



Windows PowerShell Get-Help on Cmdlet 'Set-AzApiManagementOpenIdConnectProvider'

PS:\>Get-HELP Set-AzApiManagementOpenIdConnectProvider -Full

NAME

Set-AzApiManagementOpenIdConnectProvider

SYNOPSIS

Modifies an OpenID Connect provider.

SYNTAX

```
Set-AzApiManagementOpenIdConnectProvider [-ClientId <System.String>] [-ClientSecret <System.String>] -Context  
<Microsoft.Azure.Commands.ApiManagement.ServiceManagement.Models.PsApiManagementContext> [-DefaultProfile  
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-Description  
<System.String>] [-MetadataEndpointUri <System.String>]  
[-Name <System.String>] -OpenIdConnectProviderId <System.String> [-PassThru] [-Confirm] [-WhatIf]  
[<CommonParameters>]
```

DESCRIPTION

The Set-AzApiManagementOpenIdConnectProvider cmdlet modifies an OpenID Connect provider in Azure API Management.

PARAMETERS

`-ClientId <System.String>`

Specifies the client ID of the developer console.

Required? false

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

`-ClientSecret <System.String>`

Specifies the client secret of the developer console.

Required? false

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

`-Context <Microsoft.Azure.Commands.ApiManagement.ServiceManagement.Models.PsApiManagementContext>`

Specifies a PsApiManagementContext object.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByPropertyName, ByValue)

Accept wildcard characters? false

`-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>`

The credentials, account, tenant, and subscription used for communication with azure.

Required? false

Position? named
Default value None
Accept pipeline input? False
Accept wildcard characters? false

-Description <System.String>

Specifies a description.

Required? false
Position? named
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-MetadataEndpointUri <System.String>

Specifies a metadata endpoint URI of the provider.

Required? false
Position? named
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-Name <System.String>

Specifies a friendly name for the provider.

Required? false
Position? named
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-OpenIdConnectProviderId <System.String>

Specifies an ID for the provider that this cmdlet modifies. If you do not specify an ID, this cmdlet generates one.

Required? true
Position? named
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-PassThru <System.Management.Automation.SwitchParameter>

Indicates that this cmdlet returns the PsApiManagementOpenIdConnectProvider that this cmdlet modifies.

Required? false
Position? named
Default value False
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required? false
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required? false
Position? named
Default value False
Accept pipeline input? False

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.Commands.ApiManagement.ServiceManagement.Models.PsApiManagementContext

System.String

System.Management.Automation.SwitchParameter

OUTPUTS

Microsoft.Azure.Commands.ApiManagement.ServiceManagement.Models.PsApiManagementOpenIdConnectProvider

NOTES

----- Example 1: Change the client secret for a provider -----

```
$apimContext = New-AzApiManagementContext -ResourceGroupName "Api-Default-WestUS" -ServiceName "contoso"
```

```
Set-AzApiManagementOpenIdConnectProvider -Context $apimContext -OpenIdConnectProviderId "OICP-Provider1" -ClientSecret "NewSecret"
```

-ClientSecret "q2w3e43r45" -PassThru

This command modifies the provider that has the ID OICProvider01. The command specifies a client secret for the provider.

----- Example 2 -----

```
Set-AzApiManagementOpenIdConnectProvider -ClientId 'clientid' -ClientSecret 'q2w3e43r45' -Context  
<PsApiManagementContext> -OpenIdConnectProviderId 'OICProvider01'  
-PassThru
```

RELATED LINKS

Online

Version:

<https://learn.microsoft.com/powershell/module/az.apimanagement/set-azapimanagementopenidconnectprovider>

Get-AzApiManagementOpenIdConnectProvider

New-AzApiManagementOpenIdConnectProvider

Remove-AzApiManagementOpenIdConnectProvider