



Windows PowerShell Get-Help on Cmdlet 'Set-AzAppConfigurationKeyValue'

PS:\>Get-HELP Set-AzAppConfigurationKeyValue -Full

NAME

Set-AzAppConfigurationKeyValue

SYNOPSIS

Put a key-value.

SYNTAX

```
Set-AzAppConfigurationKeyValue -Endpoint <String> -Key <String> [-Label <String>] [-IfMatch <String>] [-IfNoneMatch
<String>] [-SyncToken <String>] [-ContentType
<String>] [-Etag <String>] [-Key1 <String>] [-Label1 <String>] [-LastModified <DateTime>] [-Locked] [-Tag <Hashtable>]
[-Value <String>] [-DefaultProfile <PSObject>]
[-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>]
[-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]
```

```
Set-AzAppConfigurationKeyValue -Endpoint <String> -Key <String> [-Label <String>] [-IfMatch <String>] [-IfNoneMatch
<String>] [-SyncToken <String>] -JsonFilePath
<String> [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend
<SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential
```

<PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

Set-AzAppConfigurationKeyValue -Endpoint <String> -Key <String> [-Label <String>] [-IfMatch <String>] [-IfNoneMatch
<String>] [-SyncToken <String>] -JsonString

<String> [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend
<SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential

<PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION

Put a key-value.

PARAMETERS

-Endpoint <String>

The endpoint of the App Configuration instance to send requests to.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Key <String>

The key of the key-value to create.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Label <String>

The label of the key-value to create.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-IfMatch <String>

Used to perform an operation only if the targeted resource's etag matches the value provided.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-IfNoneMatch <String>

Used to perform an operation only if the targeted resource's etag does not match the value provided.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SyncToken <String>

Used to guarantee real-time consistency between requests.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ContentType <String>

.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Etag <String>

.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Key1 <String>

.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Label1 <String>

.

Required? false

Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-LastModified <DateTime>

.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Locked [<SwitchParameter>]

.

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-Tag <Hashtable>

Dictionary of <string>

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Value <String>

.

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-JsonFilePath <String>

Path of Json file supplied to the Put operation

Required?	true
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-JsonString <String>

Json string supplied to the Put operation

Required?	true
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required?	false
Position?	named
Default value	

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.AppConfigurationdata.Models.IKeyValue

----- EXAMPLE 1 -----

```
PS C:\>Set-AzAppConfigurationKeyValue -Endpoint $endpoint -Key keyName2 -Label label -Value value2
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.appconfiguration/set-azappconfigurationkeyvalue>

