



Windows PowerShell Get-Help on Cmdlet 'Set-AzRecoveryServicesAsrAlertSetting'

PS:\>Get-HELP Set-AzRecoveryServicesAsrAlertSetting -Full

NAME

Set-AzRecoveryServicesAsrAlertSetting

SYNOPSIS

Configure Azure Site Recovery notification settings (email notification) for the vault.

SYNTAX

```
Set-AzRecoveryServicesAsrAlertSetting [-CustomEmailAddress <System.String[]>] [-DefaultProfile
    <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-LocaleID
    <System.String>] [-Confirm] [-WhatIf] [<CommonParameters>]
```

```
Set-AzRecoveryServicesAsrAlertSetting [-CustomEmailAddress <System.String[]>] [-DefaultProfile
    <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>]
-EnableEmailSubscriptionOwner [-LocaleID <System.String>] [-Confirm]
    [-WhatIf] [<CommonParameters>]
```

```
Set-AzRecoveryServicesAsrAlertSetting [-CustomEmailAddress <System.String[]>] [-DefaultProfile
    <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>]
-DisableEmailToSubscriptionOwner [-LocaleID <System.String>] [-Confirm]
```

[-WhatIf] [<CommonParameters>]

Set-AzRecoveryServicesAsrAlertSetting

[-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] -DisableNotification

[-Confirm] [-WhatIf] [<CommonParameters>]

DESCRIPTION

The Set-AzRecoveryServicesAsrNotificationSetting cmdlet configures Azure Site Recovery notification settings (email notification) for the vault.

PARAMETERS

-CustomEmailAddress <System.String[]>

Alert / Notification sent to emails.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-DisableEmailToSubscriptionOwner <System.Management.Automation.SwitchParameter>

Switch parameter specifies enable notification to subscription owner.

Required? true
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

-DisableNotification <System.Management.Automation.SwitchParameter>

Flag to disable all notification.

Required? true
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

-EnableEmailSubscriptionOwner <System.Management.Automation.SwitchParameter>

Switch parameter specifies enable notification to subscription owner.

Required? true
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

-LocaleID <System.String>

Email language of alert /notification to user(supported culture codes from microsoft).

Required? false
Position? named
Default value None
Accept pipeline input? False
Accept wildcard characters? false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

None

OUTPUTS

Microsoft.Azure.Commands.RecoveryServices.SiteRecovery.ASRAlertSetting

NOTES

----- Example 1 -----

Set-AzRecoveryServicesAsrAlertSetting -DisableNotification

CustomEmailAddress EmailSubscriptionOwner Locale

{}	Off	en-US
----	-----	-------

Disable notification.

----- Example 2 -----

Set-AzRecoveryServicesAsrAlertSetting -CustomEmailAddress "abcxxxx@xxxx.com" -EnableEmailSubscriptionOwner

CustomEmailAddress EmailSubscriptionOwner Locale

{abcxxxx@xxxx.com}	On	en-US
--------------------	----	-------

Set notification for custom email address(s) and for subscription owner.

----- Example 3 -----

Set-AzRecoveryServicesAsrAlertSetting -CustomEmailAddress 'abcxxxx@xxxx.com' -DisableEmailToSubscriptionOwner

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.recoveryservices/set-azrecoveryservicesasralertsetting>