



Windows PowerShell Get-Help on Cmdlet 'Set-AzRecoveryServicesAsrVaultContext'

PS:\>Get-HELP Set-AzRecoveryServicesAsrVaultContext -Full

NAME

Set-AzRecoveryServicesAsrVaultContext

SYNOPSIS

Sets the Recovery Services vault context to be used for subsequent Azure Site Recovery operations in the current PowerShell session.

SYNTAX

```
Set-AzRecoveryServicesAsrVaultContext [-DefaultProfile  
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] -Vault  
<Microsoft.Azure.Commands.RecoveryServices.ARSVault> [-Confirm] [-WhatIf] [<CommonParameters>]
```

DESCRIPTION

The Set-AzRecoveryServicesAsrVaultContext cmdlet sets the Azure Site Recovery vault context for further operations.

PARAMETERS

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with azure.

Required? false
Position? named
Default value None
Accept pipeline input? False
Accept wildcard characters? false

-Vault <Microsoft.Azure.Commands.RecoveryServices.ARSVault>

The Recovery Services vault object corresponding to the Recovery Services vault.

Required? true
Position? named
Default value None
Accept pipeline input? True (ByValue)
Accept wildcard characters? false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required? false
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required? false
Position? named
Default value False
Accept pipeline input? False

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.Commands.RecoveryServices.ARSVault

OUTPUTS

Microsoft.Azure.Commands.RecoveryServices.SiteRecovery.ASRVaultSettings

NOTES

----- Example 1 -----

```
$vaultSettings = Set-AzRecoveryServicesAsrVaultContext -Vault $RecoveryServicesVault
```

Sets the vault context to the specified Recovery Services vault for subsequent Azure Site Recovery operations in the current PowerShell session.

