



Windows PowerShell Get-Help on Cmdlet 'Set-AzSqlInstanceDatabase'

PS:\>Get-HELP Set-AzSqlInstanceDatabase -Full

NAME

Set-AzSqlInstanceDatabase

SYNOPSIS

Updated an Azure SQL Managed Instance database.

SYNTAX

```

Set-AzSqlInstanceDatabase [-InputObject]
<Microsoft.Azure.Commands.Sql.ManagedDatabase.Model.AzureSqlManagedDatabaseModel> [-AsJob] [-DefaultProfile
    <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] -Tag
<System.Collections.Hashtable> [-Confirm] [-WhatIf]
[<CommonParameters>]

Set-AzSqlInstanceDatabase [-Name] <System.String> [-InstanceName] <System.String> [-ResourceGroupName]
<System.String> [-AsJob] [-DefaultProfile
    <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] -Tag
<System.Collections.Hashtable> [-Confirm] [-WhatIf]
[<CommonParameters>]

```

```

Set-AzSqlInstanceDatabase [[-Name] <System.String> [-InstanceObject]
<Microsoft.Azure.Commands.Sql.ManagedInstance.Model.AzureSqlManagedInstanceModel> [-AsJob]
[-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] -Tag
<System.Collections.Hashtable> [-Confirm] [-WhatIf]
[<CommonParameters>]

```

```

Set-AzSqlInstanceDatabase [-ResourceId] <System.String> [-AsJob] [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] -Tag
<System.Collections.Hashtable> [-Confirm] [-WhatIf]
[<CommonParameters>]

```

DESCRIPTION

Set-AzSqlInstanceDatabase cmdlet updates properties on the given managed database.

PARAMETERS

-AsJob <System.Management.Automation.SwitchParameter>

Run cmdlet in the background

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-InputObject <Microsoft.Azure.Commands.Sql.ManagedDatabase.Model.AzureSqlManagedDatabaseModel>

The database object

Required? true

Position? 0

Default value None

Accept pipeline input? True (ByValue)

Accept wildcard characters? false

-InstanceName <System.String>

The name of the instance.

Required? true

Position? 1

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Name <System.String>

The name of the instance database to create.

Required? true

Position? 0

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-ResourceGroupName <System.String>

The name of the resource group.

Required? true

Position? 2
Default value None
Accept pipeline input? False
Accept wildcard characters? false

-ResourceId <System.String>

The instance database resource id

Required? true
Position? 0
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-Tag <System.Collections.Hashtable>

The tags to associate with the instance database

Required? true
Position? named
Default value None
Accept pipeline input? False
Accept wildcard characters? false

-InstanceObject <Microsoft.Azure.Commands.Sql.ManagedInstance.Model.AzureSqlManagedInstanceModel>

The managed instance object

Required? true
Position? 0
Default value None
Accept pipeline input? True (ByValue)
Accept wildcard characters? false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.Commands.Sql.ManagedDatabase.Model.AzureSqlManagedDatabaseModel

Microsoft.Azure.Commands.Sql.ManagedInstance.Model.AzureSqlManagedInstanceModel

System.String

OUTPUTS

Microsoft.Azure.Commands.Sql.ManagedDatabase.Model.AzureSqlManagedDatabaseModel

NOTES

----- Example 1 -----

```
Set-AzSqlInstanceDatabase -Name "name1" -InstanceName "instance1" -ResourceGroupName "rg1" -Tags
@{tag1="value1"}
```

```
Location           : westcentralus
Tags               : {[tag1, value1]}
Collation          : SQL_Latin1_General_CP1_CI_AS
Status             : Online
RestorePointInTime :
DefaultSecondaryLocation : westus2
CatalogCollation   :
CreateMode          :
StorageContainerUri :
StorageContainerSasToken :
SourceDatabaseId    :
FailoverGroupId     :
RecoverableDatabaseId :
RestorableDroppedDatabaseId :
LongTermRetentionBackupResourceId :
AutoCompleteRestore :
LastBackupName      :
```

ResourceGroupName : rg1

ManagedInstanceName : instance1

Name : name1

CreationDate : 4/11/2022 5:26:30 PM

EarliestRestorePoint : 6/14/2022 5:07:14 PM

Id :

/subscriptions/subscription_id/resourceGroups/rg1/providers/Microsoft.Sql/managedInstances/instance1/databases/name1

This command sets tags to existing managed database.

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.sql/set-azsqlinstancedatabase>

New-AzSqlInstanceDatabase