



Windows PowerShell Get-Help on Cmdlet 'Set-AzSqlServerAdvisorAutoExecuteStatus'

PS:\>Get-HELP Set-AzSqlServerAdvisorAutoExecuteStatus -Full

NAME

Set-AzSqlServerAdvisorAutoExecuteStatus

SYNOPSIS

Updates the auto execute status of an Azure SQL Server Advisor.

SYNTAX

```
Set-AzSqlServerAdvisorAutoExecuteStatus [-ResourceGroupName] <System.String> -AdvisorName <System.String>
-AutoExecuteStatus {Enabled | Disabled | Default}
[-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>]
-ServerName <System.String> [-Confirm] [-WhatIf]
[<CommonParameters>]
```

DESCRIPTION

The Set-AzSqlServerAdvisorAutoExecuteStatus cmdlet sets the auto execute property for an Azure SQL Server Advisor.

-AdvisorName <System.String>

Specifies the name of the advisor for which this cmdlet updates the auto execute status.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-AutoExecuteStatus <Microsoft.Azure.Commands.Sql.Advisor.Cmdlet.AdvisorAutoExecuteStatus>

Specifies the value to which this cmdlet updates the auto execute status. The acceptable values for this parameter are:

- Enabled

- Disabled

- Default

Required? true

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with azure

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-ResourceGroupName <System.String>

Specifies the name of the resource group of the server.

Required? true

Position? 0

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-ServerName <System.String>

Specifies the name of the server.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

System.String

Microsoft.Azure.Commands.Sql.Advisor.Cmdlet.AdvisorAutoExecuteStatus

OUTPUTS

Microsoft.Azure.Commands.Sql.Advisor.Model.AzureSqlServerAdvisorModel

NOTES

* Keywords: azure, azurearm, arm, resource, management, manager, sql, server, mssql, advisor

----- Example 1: Enable auto execute for an Advisor -----

```
Set-AzSqlServerAdvisorAutoExecuteStatus -ResourceGroupName "WIRunnersProd" -ServerName  
"wi-runner-australia-east" -AdvisorName "CreateIndex" -AutoExecuteStatus Enabled
```

ResourceGroupName : WIRunnersProd

ServerName : wi-runner-australia-east

AdvisorName : CreateIndex
AdvisorStatus : GA
AutoExecuteStatus : Enabled
AutoExecuteStatusInheritedFrom : Server
LastChecked : 8/1/2016 2:36:47 PM
RecommendationsStatus : Ok
RecommendedActions : {}

This command enables the auto execute status of an Advisor named CreateIndex.

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.sql/set-azsqlserveradvisorautoexecutestatus>

[Get-AzSqlServerAdvisor](#)

SQL Database Documentation <https://learn.microsoft.com/azure/sql-database/>