



Windows PowerShell Get-Help on Cmdlet 'Set-AzSqlServerDnsAlias'

PS:\>Get-HELP Set-AzSqlServerDnsAlias -Full

NAME

Set-AzSqlServerDnsAlias

SYNOPSIS

Modifies the server to which Azure SQL Server DNS Alias is pointing

SYNTAX

```
Set-AzSqlServerDnsAlias [-ResourceGroupName] <System.String> [-AsJob] [-DefaultProfile  
    <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] -Name  
<System.String> -SourceServerName <System.String>  
    -SourceServerResourceGroupName <System.String> -SourceServerSubscriptionId <System.Guid> -TargetServerName  
<System.String> [-Confirm] [-WhatIf] [<CommonParameters>]
```

DESCRIPTION

This command is updating the server to which alias is pointing. This command needs to be issued while logged into subscription where new server to which alias is going to point is located.

PARAMETERS

-AsJob <System.Management.Automation.SwitchParameter>

Run cmdlet in the background

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Name <System.String>

The Azure Sql Server Dns Alias name.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-ResourceGroupName <System.String>

The name of the resource group.

Required? true

Position? 0
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-SourceServerName <System.String>

The name of Azure Sql Server to which alias is currently pointing.

Required? true
Position? named
Default value None
Accept pipeline input? False
Accept wildcard characters? false

-SourceServerResourceGroupName <System.String>

The name of resource group of the source server.

Required? true
Position? named
Default value None
Accept pipeline input? False
Accept wildcard characters? false

-SourceServerSubscriptionId <System.Guid>

The subscription id of the source server

Required? true
Position? named
Default value None
Accept pipeline input? False
Accept wildcard characters? false

-TargetServerName <System.String>

The name of Azure Sql Server to which alias should point.

Required?	true
Position?	named
Default value	None
Accept pipeline input?	False
Accept wildcard characters?	false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

System.String

OUTPUTS

Microsoft.Azure.Commands.Sql.ServerDnsAlias.Model.AzureSqlServerDnsAliasModel

NOTES

----- Example 1 -----

```
Set-AzSqlServerDnsAlias -ResourceGroupName rg -DnsAliasName aliasName -TargetServerName newServer  
-SourceServerName oldServer -SourceServerResourceGroupName  
SourceServerRG -SourceServerSubscriptionId 0000-0000-0000-0000
```

This command is updating alias which was previously pointing to oldServer to point to server newServer

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.sql/set-azsqlserverdnsalias>