



Windows PowerShell Get-Help on Cmdlet 'Set-AzSynapseManagedIdentitySqlControlSetting'

PS:\>Get-HELP Set-AzSynapseManagedIdentitySqlControlSetting -Full

NAME

Set-AzSynapseManagedIdentitySqlControlSetting

SYNOPSIS

Updates managed identity SQL control settings to workspace.

SYNTAX

```

Set-AzSynapseManagedIdentitySqlControlSetting [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] -Enabled
[System.Boolean] [-ResourceGroupName <System.String>] -WorkspaceName <System.String> [-Confirm] [-WhatIf]
[<CommonParameters>]

```

```

Set-AzSynapseManagedIdentitySqlControlSetting [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] -Enabled
[System.Boolean] -ResourceId <System.String> [-Confirm] [-WhatIf] [<CommonParameters>]

```

```

Set-AzSynapseManagedIdentitySqlControlSetting [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] -Enabled
[System.Boolean] -WorkspaceObject <Microsoft.Azure.Commands.Synapse.Models.PSSynapseWorkspace> [-Confirm]

```

[-WhatIf] [<CommonParameters>]

DESCRIPTION

The Set-AzSynapseManagedIdentitySqlControlSetting updates managed identity SQL control settings to workspace.

PARAMETERS

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Enabled <System.Boolean>

Indicates whether to enable managed identity SQL control setting. Specify \$True to enable managed identity SQL control setting, or \$False to disable managed identity SQL control setting.

Required? true

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-ResourceGroupName <System.String>

Resource group name.

Required? false

Position? named

Default value None
Accept pipeline input? False
Accept wildcard characters? false

-ResourceId <System.String>

Resource identifier of Synapse workspace.

Required? true
Position? named
Default value None
Accept pipeline input? False
Accept wildcard characters? false

-WorkspaceName <System.String>

Name of Synapse workspace.

Required? true
Position? named
Default value None
Accept pipeline input? False
Accept wildcard characters? false

-WorkspaceObject <Microsoft.Azure.Commands.Synapse.Models.PSSynapseWorkspace>

workspace input object, usually passed through the pipeline.

Required? true
Position? named
Default value None
Accept pipeline input? True (ByValue)
Accept wildcard characters? false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.Commands.Synapse.Models.PSSynapseWorkspace

OUTPUTS

Microsoft.Azure.Commands.Synapse.Models.PSManagedIdentitySqlControlSettingsModel

----- Example 1 -----

```
Set-AzSynapseManagedIdentitySqlControlSetting -WorkspaceName ContosoWorkspace -Enabled $true
```

This command enables managed identity SQL control settings to workspace for workspace ContosoWorkspace.

----- Example 2 -----

```
Set-AzSynapseManagedIdentitySqlControlSetting -WorkspaceName ContosoWorkspace -Enabled $false
```

This command disables managed identity SQL control settings to workspace for workspace ContosoWorkspace.

----- Example 3 -----

```
$ws = Get-AzSynapseWorkspace -Name ContosoWorkspace
```

```
$ws | Set-AzSynapseManagedIdentitySqlControlSetting -Enabled $true
```

This command enables managed identity SQL control settings to workspace for workspace ContosoWorkspace through pipeline.

----- Example 4 -----

```
Set-AzSynapseManagedIdentitySqlControlSetting -ResourceId
```

```
/subscriptions/21686af7-58ec-4f4d-9c68-f431f4db4edd3/resourcegroups/ContosoResourceGroup/providers/Microsoft.Synapse/workspaces/ContosoWorkspace -Enabled $true
```

This command enables managed identity SQL control settings to workspace for workspace ContosoWorkspace through the workspace's resource ID.

RELATED LINKS

Online

Version:

<https://learn.microsoft.com/powershell/module/az.synapse/set-azsynapsemanagedidentitysqlcontrolsetting>