

Full credit is given to all the above companies including the Operating System that this PDF file was generated!

## Windows PowerShell Get-Help on Cmdlet 'Set-NetAdapterIPsecOffload'

PS:\>Get-HELP Set-NetAdapterIPsecOffload -Full

NAME

Set-NetAdapterIPsecOffload

### **SYNOPSIS**

Sets the IPsec offload properties of a network adapter.

## **SYNTAX**

Set-NetAdapterIPsecOffload [-Name] <String[]> [-AsJob] [-CimSession <CimSession[]>] [-Confirm] [-Enabled <Boolean>] [-IncludeHidden] [-NoRestart] [-PassThru]

[-ThrottleLimit <Int32>] [-WhatIf] [<CommonParameters>]

Set-NetAdapterIPsecOffload [-AsJob] [-CimSession < CimSession[]>] [-Confirm] [-Enabled < Boolean>] [-IncludeHidden] -InterfaceDescription < String[]> [-NoRestart]

[-PassThru] [-ThrottleLimit <Int32>] [-WhatIf] [<CommonParameters>]

Set-NetAdapterIPsecOffload [-AsJob] [-CimSession <CimSession[]>] [-Confirm] [-Enabled <Boolean>] -InputObject <CimInstance[]> [-NoRestart] [-PassThru] [-ThrottleLimit

<Int32>] [-WhatIf] [<CommonParameters>]

### **DESCRIPTION**

The Set-NetAdapterIPsecOffload cmdlet sets the IPsec offload properties of a network adapter. When IPsec offload is enabled the network adapter performs the per

packet encryption operations which reduces processor utilization. The enabled state can be set by using the Enable-NetAdapterIPsecOffload or

Disable-NetAdapterIPsecOffload cmdlet.

#### **PARAMETERS**

-AsJob [<SwitchParameter>]

Runs the cmdlet as a background job. Use this parameter to run commands that take a long time to complete. The cmdlet immediately returns an object that

represents the job and then displays the command prompt. You can continue to work in the session while the job completes. To manage the job, use the `\*-Job`

cmdlets. To get the job results, use the Receive-Job (https://go.microsoft.com/fwlink/?LinkID=113372)cmdlet. For more information about Windows PowerShellr

background jobs, see about Jobs (https://go.microsoft.com/fwlink/?LinkID=113251).

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

### -CimSession <CimSession[]>

Runs the cmdlet in a remote session or on a remote computer. Enter a computer name or a session object, such as the output of a New-CimSession

(https://go.microsoft.com/fwlink/p/?LinkId=227967)

or

[Get-CimSession](https://go.microsoft.com/fwlink/p/?LinkId=227966)cmdlet. The default is the current session on the local computer.

Required? false Page 2/7

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

## -Confirm [<SwitchParameter>]

Prompts you for confirmation before running the cmdlet.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

### -Enabled <Boolean>

Specifies the state of IPsec offload. The acceptable values for this parameter are: \$True or \$False.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

## -IncludeHidden [<SwitchParameter>]

Indicates that the cmdlet includes both visible and hidden network adapters in the operation. By default only visible network adapters are included. If a wildcard

character is used in identifying a network adapter and this parameter has been specified, then the wildcard string is matched against both hidden and visible

network adapters.

Required? false

Position? named

Default value False Page 3/7

Accept pipeline input? False

Accept wildcard characters? false

## -InputObject <CimInstance[]>

Specifies the input to this cmdlet. You can use this parameter, or you can pipe the input to this cmdlet.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByValue)

Accept wildcard characters? false

### -InterfaceDescription <String[]>

Specifies an array of network adapter interface descriptions. For a physical network adapter this is typically the name of the vendor of the network adapter

followed by a part number and description, such as `Contoso 12345 Gigabit Network Device`.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

## -Name <String[]>

Specifies an array of network adapter names.

Required? true

Position? 0

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

Indicates that the cmdlet does not restart the network adapter after completing the operation. Many advanced properties require restarting the network adapter

before the new settings take effect.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

## -PassThru [<SwitchParameter>]

Returns an object representing the item with which you are working. By default, this cmdlet does not generate any output.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

### -ThrottleLimit <Int32>

Specifies the maximum number of concurrent operations that can be established to run the cmdlet. If this parameter is omitted or a value of `0` is entered, then

Windows PowerShellr calculates an optimum throttle limit for the cmdlet based on the number of CIM cmdlets that are running on the computer. The throttle limit

applies only to the current cmdlet, not to the session or to the computer.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

### -WhatIf [<SwitchParameter>]

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

### <CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug,

ErrorAction, ErrorVariable, WarningAction, WarningVariable,

OutBuffer, PipelineVariable, and OutVariable. For more information, see

about\_CommonParameters (https:/go.microsoft.com/fwlink/?LinkID=113216).

## **INPUTS**

Microsoft.Management.Infrastructure.CimInstance#ROOT/StandardCimv2/MSFT\_NetAdapter

### IPsecOffloadV2SettingData[]

The `Microsoft.Management.Infrastructure.CimInstance` object is a wrapper class that displays Windows Management Instrumentation (WMI) objects. The path after the

pound sign ('#') provides the namespace and class name for the underlying WMI object.

## **OUTPUTS**

Microsoft.Management.Infrastructure.CimInstance#ROOT/StandardCimv2/MSFT\_NetAdapter

# IP sec Offload V2 Setting Data

The `Microsoft.Management.Infrastructure.CimInstance` object is a wrapper class that displays Windows Management Instrumentation (WMI) objects. The path after the

pound sign (`#`) provides the namespace and class name for the underlying WMI object.

Example 1: Enable IPsec offload on the specified network adapter

PS C:\> Set-NetAdapterIPsecOffload -Name "MyAdapter" -Enabled \$True

This command enables IPsec offload on the network adapter named MyAdapter and restarts the network adapter. The Enable-NetAdapterIPsecOffload cmdlet is the preferred cmdlet to perform this operation.

### **RELATED LINKS**

Online Version:

https://learn.microsoft.com/powershell/module/netadapter/set-netadapteripsecoffload?view=windowsserver2022-ps&wt.mc\_i d=ps-gethelp

Disable-NetAdapterIPsecOffload

Enable-NetAdapterIPsecOffload

Get-NetAdapterIPsecOffload