



Windows PowerShell Get-Help on Cmdlet 'Set-SFTPContent'

PS:\>Get-HELP Set-SFTPContent -Full

NAME

Set-SFTPContent

SYNOPSIS

SYNTAX

Set-SFTPContent [-SessionId] <Int32[]> [-Path] <String> [-Value] <Object> [-Encoding {ASCII | Unicode | UTF7 | UTF8 | UTF32 | BigEndianUnicode}] [-Append]
[<CommonParameters>]

Set-SFTPContent [-SFTPSession] <SftpSession[]> [-Path] <String> [-Value] <Object> [-Encoding {ASCII | Unicode | UTF7 | UTF8 | UTF32 | BigEndianUnicode}] [-Append]
[<CommonParameters>]

DESCRIPTION

Set the content of a specific item on a remote server through an SFTP session.

PARAMETERS

-SessionId <Int32[]>

Session Id of an existing SFTPSession.

Required? true

Position? 1

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-SFTPSession <SftpSession[]>

Existing SFTPSession object.

Required? true

Position? 1

Default value None

Accept pipeline input? True (ByValue)

Accept wildcard characters? false

-Path <String>

Path to existing remote file

Required? true

Position? 2

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-Value <Object>

Content to upload

Required? true

Position? 3
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-Encoding <String>

Content encoding

Required? false
Position? named
Default value UTF8
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-Append [<SwitchParameter>]

Append content to file

Required? false
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

OUTPUTS

Renci.SshNet.Sftp.SftpFile

NOTES

----- Example 1 -----

```
PS C:\> Set-SFTPContent -SessionId 0 -Path /tmp/example.txt -Value "My example message`n"
```

Set the content of /tmp/example.txt to "My example message`n" in sftp session 0

RELATED LINKS

Online Version: <https://github.com/darkoperator/Posh-SSH/tree/master/docs>