



Windows PowerShell Get-Help on Cmdlet 'Start-AzRecoveryServicesAsrTestFailoverCleanupJob'

PS:\>Get-HELP Start-AzRecoveryServicesAsrTestFailoverCleanupJob -Full

NAME

Start-AzRecoveryServicesAsrTestFailoverCleanupJob

SYNOPSIS

Starts the test failover cleanup operation.

SYNTAX

```
Start-AzRecoveryServicesAsrTestFailoverCleanupJob [-Comment <System.String>] [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] -RecoveryPlan
<Microsoft.Azure.Commands.RecoveryServices.SiteRecovery.ASRRecoveryPlan> [-Confirm] [-WhatIf]
[<CommonParameters>]
```

```
Start-AzRecoveryServicesAsrTestFailoverCleanupJob [-Comment <System.String>] [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>]
-ReplicationProtectedItem
<Microsoft.Azure.Commands.RecoveryServices.SiteRecovery.ASRReplicationProtectedItem> [-Confirm] [-WhatIf]
[<CommonParameters>]
```

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] -ResourceId
<System.String> [-Confirm] [-WhatIf] [<CommonParameters>]

DESCRIPTION

The Start-AzRecoveryServicesAsrTestFailoverCleanupJob cmdlet starts the test failover cleanup operation on a replication protected item or recovery plan on which a test failover has been performed.

PARAMETERS

-Comment <System.String>

User Comment for Test Failover.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-RecoveryPlan <Microsoft.Azure.Commands.RecoveryServices.SiteRecovery.ASRRecoveryPlan>

Recovery Plan to perform the test failover cleanup on.

Required? true

Position? named
Default value None
Accept pipeline input? True (ByValue)
Accept wildcard characters? false

-ReplicationProtectedItem <Microsoft.Azure.Commands.RecoveryServices.SiteRecovery.ASRReplicationProtectedItem>

Replication Protected Item to perform the test failover cleanup on.

Required? true
Position? named
Default value None
Accept pipeline input? True (ByValue)
Accept wildcard characters? false

-ResourceId <System.String>

Resource Id of replication protected item / recovery plan for cleaningup test failover.

Required? true
Position? named
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required? false
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

System.String

Microsoft.Azure.Commands.RecoveryServices.SiteRecovery.ASRRecoveryPlan

Microsoft.Azure.Commands.RecoveryServices.SiteRecovery.ASRReplicationProtectedItem

OUTPUTS

Microsoft.Azure.Commands.RecoveryServices.SiteRecovery.ASRJob

NOTES

----- Example 1 -----

Start-AzRecoveryServicesAsrTestFailoverCleanupJob -RecoveryPlan \$recoveryPlan -Comment "testing done"

----- Example 2 -----

Start-AzRecoveryServicesAsrTestFailoverCleanupJob -Comment 'testing done' -ReplicationProtectedItem \$rpi

RELATED LINKS

Online

Version:

<https://learn.microsoft.com/powershell/module/az.recoveryservices/start-azrecoveryservicesasrtestfailovercleanupjob>