



## ***Windows PowerShell Get-Help on Cmdlet 'Start-AzSynapseKustoPool'***

***PS:\>Get-HELP Start-AzSynapseKustoPool -Full***

### NAME

Start-AzSynapseKustoPool

### SYNOPSIS

Starts a Kusto pool.

### SYNTAX

Start-AzSynapseKustoPool -Name <String> -ResourceGroupName <String> [-SubscriptionId <String>] -WorkspaceName <String> [-DefaultProfile <PSObject>] [-AsJob] [-Break]

[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-PassThru] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]

[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

Start-AzSynapseKustoPool -InputObject <ISynapseIdentity> [-DefaultProfile <PSObject>] [-AsJob] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend

<SendAsyncStep[]>] [-NoWait] [-PassThru] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]

[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

## DESCRIPTION

Starts a Kusto pool.

## PARAMETERS

-Name <String>

The name of the Kusto pool.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

The ID of the target subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

**-WorkspaceName <String>**

The name of the workspace

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

**-InputObject <ISynapseIdentity>**

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

**-DefaultProfile <PSObject>**

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

**-AsJob [<SwitchParameter>]**

Run the command as a job

Required? false

Position?                  named  
Default value              False  
Accept pipeline input?    false  
Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required?                  false  
Position?                  named  
Default value              False  
Accept pipeline input?    false  
Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required?                  false  
Position?                  named  
Default value  
Accept pipeline input?    false  
Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required?                  false  
Position?                  named  
Default value  
Accept pipeline input?    false  
Accept wildcard characters? false

-NoWait [<SwitchParameter>]

Run the command asynchronously

|                             |       |
|-----------------------------|-------|
| Required?                   | false |
| Position?                   | named |
| Default value               | False |
| Accept pipeline input?      | false |
| Accept wildcard characters? | false |

-PassThru [<SwitchParameter>]

Returns true when the command succeeds

|                             |       |
|-----------------------------|-------|
| Required?                   | false |
| Position?                   | named |
| Default value               | False |
| Accept pipeline input?      | false |
| Accept wildcard characters? | false |

-Proxy <Uri>

The URI for the proxy server to use

|                             |       |
|-----------------------------|-------|
| Required?                   | false |
| Position?                   | named |
| Default value               |       |
| Accept pipeline input?      | false |
| Accept wildcard characters? | false |

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

|                        |       |
|------------------------|-------|
| Required?              | false |
| Position?              | named |
| Default value          |       |
| Accept pipeline input? | false |

Accept wildcard characters? false

#### -ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

#### -WhatIf [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -Confirm [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### <CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about\_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

## INPUTS

Microsoft.Azure.PowerShell.Cmdlets.Synapse.Models.ISynapseIdentity

## OUTPUTS

System.Boolean

## NOTES

### COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about\_Hash\_Tables.

INPUTOBJECT <ISynapseIdentity>: Identity Parameter

[AttachedDatabaseConfigurationName <String>]: The name of the attached database configuration.

[DataConnectionName <String>]: The name of the data connection.

[DatabaseName <String>]: The name of the database in the Kusto pool.

[Id <String>]: Resource identity path

[KustoPoolName <String>]: The name of the Kusto pool.

[Location <String>]: The name of Azure region.

[PrincipalAssignmentName <String>]: The name of the Kusto principalAssignment.

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[SubscriptionId <String>]: The ID of the target subscription.

[WorkspaceName <String>]: The name of the workspace

----- EXAMPLE 1 -----

PS C:\>Start-AzSynapseKustoPool -ResourceGroupName testrg -WorkspaceName testws -Name testnewkustopool

#### RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.synapse/start-azsynapsekustopool>