



python



PowerShell

FPDF Library
PDF generator

Full credit is given to the above companies including the OS that this PDF file was generated!

PowerShell Get-Help on command 'Stop-AppvClientConnectionGroup'

PS C:\Users\wahid> Get-Help Stop-AppvClientConnectionGroup

NAME

Stop-AppvClientConnectionGroup

SYNOPSIS

Shuts down the shared virtual environment of a connection group.

SYNTAX

Stop-AppvClientConnectionGroup [-ConnectionGroup] <AppvClientConnectionGroup>
[-Global] [<CommonParameters>]

Stop-AppvClientConnectionGroup [-GroupId] <Guid> [-VersionId] <Guid> [-Global]
[<CommonParameters>]

Stop-AppvClientConnectionGroup [-Name] <String> [-Global] [<CommonParameters>]

DESCRIPTION

The Stop-AppvClientConnectionGroup cmdlet shuts down the shared virtual environment of a connection group. All running processes in the connection group virtual environment are shutdown.

PARAMETERS

-ConnectionGroup <AppvClientConnectionGroup>

Specifies an App-V Connection Group object.

-Global [<SwitchParameter>]

Indicates that the cmdlet shuts down virtual environments for the specified connection groups for all users on the computer. Usage of the Global parameter requires administrative credentials.

-GroupId <Guid>

Specifies the group ID of a specific connection group.

-Name <String>

Specifies the name of the Microsoft Application Virtualization (App-V) connection group.

-VersionId <Guid>

Specifies a GUID that differentiates a connection group version from other versions, whether older, newer, or of a different lineage. If you do not specify this parameter, the cmdlet operates on all versions of the connection group.

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

--- Example 1: Stop a virtual environment for a named group ---

```
PS C:\> Stop-AppvClientConnectionGroup -Name "MyGroup"
```

This command stops the virtual environment of the enabled connection group that has the name MyGroup.

Example 2: Stop a virtual environment for a group by using its ID

```
PS C:\> Stop-AppvClientConnectionGroup -GroupID  
793afd37-bd68-4ea1-859a-669f6afd0aa8
```

This command stops the virtual environment of the enabled connection group that has the group ID 793afd37-bd68-4ea1-859a-669f6afd0aa8.

Example 3: Stop virtual environment for groups with names that match a string

```
PS C:\> Get-AppvClientConnectionGroup -Name "MyGr*" |  
Stop-AppvClientConnectionGroup
```

This command gets all of the enabled connection groups that have the string MyGr in the name, and then stops each of their virtual environments.

REMARKS

To see the examples, type: "get-help Stop-AppvClientConnectionGroup -examples".

For more information, type: "get-help Stop-AppvClientConnectionGroup -detailed".

For technical information, type: "get-help Stop-AppvClientConnectionGroup -full".

For online help, type: "get-help Stop-AppvClientConnectionGroup -online"