



python



PowerShell

FPDF Library

PDF generator

Full credit is given to the above companies including the OS that this PDF file was generated!

PowerShell Get-Help on command 'Stop-AppvClientPackage'

PS C:\Users\wahid> Get-Help Stop-AppvClientPackage

NAME

Stop-AppvClientPackage

SYNOPSIS

Shuts down virtual environments for specified packages.

SYNTAX

Stop-AppvClientPackage [-Name] <String> [[-Version] <String>] [-Global]
[<CommonParameters>]

Stop-AppvClientPackage [-Package] <AppvClientPackage> [-Global]
[<CommonParameters>]

Stop-AppvClientPackage [-PackageId] <Guid> [-VersionId] <Guid> [-Global]
[<CommonParameters>]

DESCRIPTION

The Stop-AppvClientPackage cmdlet shuts down the virtual environment for the specified packages. All applications and processes within that package are

forced to shut down. Any unsaved application data is lost.

PARAMETERS

-Global [<SwitchParameter>]

Specifies that the cmdlet shuts down virtual environments for the specified packages for all users on the computer. Usage of the Global parameter requires administrative credentials.

-Name <String>

Specifies the friendly name of the package given during Sequencing time. This value is obtained from the package manifest.

-Package <AppvClientPackage>

Specifies an App-V package.

-PackageId <Guid>

Specifies a GUID that uniquely identifies the package. It can be found in the package manifest or by opening the package in the Microsoft Application Virtualization (App-V) Sequencer. The package ID is shared by all versions of a package.

-Version <String>

Specifies the version of an App-V package in a lineage. If you do not specify this parameter, the cmdlet operates on all available versions of the package on the computer.

-VersionId <Guid>

Specifies a GUID that differentiates a package version from other versions, whether older, newer, or of a different lineage. If you do not specify this parameter, the cmdlet operates on all versions of the package.

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

Example 1: Shut down a virtual environment for a version of a package

```
PS C:\> Stop-AppvClientPackage -Name "MyPackage" -Version 2
```

This command shuts down the virtual environment of version 2 of package named MyPackage.

Example 2: Shut down a virtual environment for all versions of a package

```
PS C:\> Get-AppvClientPackage -Name "MyPackage" | Stop-AppvClientPackage
```

This command gets all versions of the package named MyPackage, and then shuts down the virtual environment for those results.

REMARKS

To see the examples, type: "get-help Stop-AppvClientPackage -examples".

For more information, type: "get-help Stop-AppvClientPackage -detailed".

For technical information, type: "get-help Stop-AppvClientPackage -full".

For online help, type: "get-help Stop-AppvClientPackage -online"