



Full credit is given to all the above companies including the Operating System that this PDF file was generated!

Windows PowerShell Get-Help on Cmdlet 'Stop-AzDataFactoryV2PipelineRun'

PS:\>Get-HELP Stop-AzDataFactoryV2PipelineRun -Full

NAME

Stop-AzDataFactoryV2PipelineRun

SYNOPSIS

Stops a pipeline run in a data factory.

SYNTAX

```
Stop-AzDataFactoryV2PipelineRun [-DataFactory] <Microsoft.Azure.Commands.DataFactoryV2.Models.PSDataFactory>
[-PipelineRunId] <System.String> [-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-PassThru]
[-Confirm] [-WhatIf] [<CommonParameters>]

Stop-AzDataFactoryV2PipelineRun [-ResourceGroupName] <System.String> [-DataFactoryName] <System.String>
[-PipelineRunId] <System.String> [-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-PassThru]
[-Confirm] [-WhatIf] [<CommonParameters>]
```

```
Stop-AzDataFactoryV2PipelineRun [-InputObject] <Microsoft.Azure.Commands.DataFactoryV2.Models.PSPipelineRun>
[-DefaultProfile]
```

```
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer> [-PassThru]  
[-Confirm] [-WhatIf] [<CommonParameters>]
```

DESCRIPTION

The Stop-AzDataFactoryV2PipelineRun cmdlet stops a pipeline run in a data factory specified with the pipeline run ID.

PARAMETERS

-DataFactory <Microsoft.Azure.Commands.DataFactoryV2.Models.PSDataFactory>

The data factory object.

Required? true

Position? 0

Default value None

Accept pipeline input? True (ByValue)

Accept wildcard characters? false

-DataFactoryName <System.String>

The data factory name.

Required? true

Position? 1

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-InputObject <Microsoft.Azure.Commands.DataFactoryV2.Models.PSPipelineRun>

The Run ID of the pipeline.

Required? true

Position? 0

Default value None

Accept pipeline input? True (ByValue)

Accept wildcard characters? false

-PassThru <System.Management.Automation.SwitchParameter>

If specified the cmdlet write true in case operation succeeds.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-PipelineRunId <System.String>

The Run ID of the pipeline.

Required? true

Position? 2

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-ResourceGroupName <System.String>

The resource group name.

Required? true
Position? 0
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required? false
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required? false
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkId=113216>).

INPUTS

Microsoft.Azure.Commands.DataFactoryV2.Models.PSPipelineRun

System.String

Microsoft.Azure.Commands.DataFactoryV2.Models.PSDataFactory

OUTPUTS

System.Boolean

NOTES

----- Example 1 -----

```
Stop-AzDataFactoryV2PipelineRun -ResourceGroupName "ADF" -DataFactoryName "WikiADF" -PipelineRunId  
b9730a13-aa12-4926-a8b3-8e3a974ab0bd
```

Confirm

Are you sure you want to stop pipeline run 'b9730a13-aa12-4926-a8b3-8e3a974ab0bd' in data factory 'WikiADF'?

[Y] Yes [N] No [S] Suspend [?] Help (default is "Y"): y

true

This command stops the pipeline run with id b9730a13-aa12-4926-a8b3-8e3a974ab0bd in the factory WikiADF.

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.datafactory/stop-azdatafactoryv2pipelinerun>