



Windows PowerShell Get-Help on Cmdlet 'Stop-PcsvDevice'

PS:\>Get-HELP Stop-PcsvDevice -Full

NAME

Stop-PcsvDevice

SYNOPSIS

Shuts down a remote hardware device.

SYNTAX

```
Stop-PcsvDevice [-TargetAddress] <String> [-Credential] <PSCredential> [-ManagementProtocol] {WSMan | IPMI} [[-Port]
<UInt16>] [-AsJob] [-Authentication {Default |
    Basic | Digest}] [-CimSession <CimSession[]>] [-Confirm] [-PassThru] [-ShutdownType {Forced | Graceful}]
[-SkipCACheck] [-SkipCNCheck] [-SkipRevocationCheck]
[-ThrottleLimit <Int32>] [-TimeoutSec <UInt32>] [-UseSSL] [-WhatIf] [<CommonParameters>]
```

```
Stop-PcsvDevice [-AsJob] [-CimSession <CimSession[]>] [-Confirm] -InputObject <CimInstance[]> [-PassThru]
[-ShutdownType {Forced | Graceful}] [-ThrottleLimit <Int32>]
[-WhatIf] [<CommonParameters>]
```

```
Stop-PcsvDevice [-AsJob] [-CimSession <CimSession[]>] [-Confirm] [-PassThru] [-ShutdownType {Forced | Graceful}]
[-ThrottleLimit <Int32>] [-TimeoutSec <UInt32>]
```

[-WhatIf] [<CommonParameters>]

DESCRIPTION

The Stop-PcsvDevice cmdlet shuts down a remote hardware device by using Web Services for Management (WS-Management) or Intelligent Platform Management Interface (IPMI). The cmdlet puts the device in the Disabled state, which corresponds to a hard shutdown of the hardware device. Specify the remote hardware device by the management name or IP address, provide credentials necessary to shut down the remote hardware device, and specify which management protocol to use. The credentials must have administrator permissions on the remote hardware device.

PARAMETERS

-AsJob [<SwitchParameter>]

Runs the cmdlet as a background job. Use this parameter to run commands that take a long time to complete.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-Authentication <Authentication>

Specifies an authentication method to use for devices managed by using WS-Management. Do not specify this parameter for devices managed by using IPMI. The acceptable values for this parameter are:

- Basic

- Digest

- Default

If you specify Default for this parameter and a value of WSMAN for the ManagementProtocol parameter, the cmdlet uses Basic authentication.

Required?	false
Position?	named
Default value	None
Accept pipeline input?	True (ByPropertyName)
Accept wildcard characters?	false

-CimSession <CimSession[]>

Runs the cmdlet in a remote session or on a remote computer. Enter a computer name or a session object, such as the output of a New-CimSession

(<https://go.microsoft.com/fwlink/p/?LinkId=227967>) or

[Get-CimSession](<https://go.microsoft.com/fwlink/p/?LinkId=227966>)cmdlet. The default is the current session on the local computer.

Required?	false
Position?	named
Default value	None
Accept pipeline input?	False
Accept wildcard characters?	false

-Confirm [<SwitchParameter>]

Prompts you for confirmation before running the cmdlet.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

`-Credential <PSCredential>`

Specifies a PSCredential object based on a user name and password. To obtain a PSCredential object, use the Get-Credential cmdlet. For more information, type

``Get-Help Get-Credential``. This parameter specifies the credential for the remote hardware device.

Required?	true
Position?	2
Default value	None
Accept pipeline input?	True (ByPropertyName)
Accept wildcard characters?	false

`-InputObject <CimInstance[]>`

Specifies the input object that is used in a pipeline command.

Required?	true
Position?	named
Default value	None
Accept pipeline input?	True (ByValue)
Accept wildcard characters?	false

`-ManagementProtocol <ManagementProtocol>`

Specifies a management protocol used to communicate with a device. The acceptable values for this parameter are:

- WSMAN

- IPMI

Refer to your hardware documentation for supported management protocols.

Specify WSMAN for devices that represent information by using Systems Management Architecture for Server Hardware (SMASH), Desktop and mobile Architecture for

System Hardware (DASH), or Physical Computer System View profiles.

Required?	true
Position?	3
Default value	None
Accept pipeline input?	True (ByPropertyName)
Accept wildcard characters?	false

-PassThru [<SwitchParameter>]

Returns an object representing the item with which you are working. By default, this cmdlet does not generate any output.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

-Port <UInt16>

Specifies a port on the remote computer to use for the management connection. If you do not specify a port, the cmdlet uses the following default values:

- IPMI and WSMAN over HTTP. Port 623. - WSMAN over HTTPS. Port 664.

Required?	false
Position?	4
Default value	None
Accept pipeline input?	True (ByPropertyName)
Accept wildcard characters?	false

-ShutdownType <PossibleShutdownTypes>

Required?	false
Position?	named
Default value	None
Accept pipeline input?	False
Accept wildcard characters?	false

-SkipCACheck [<SwitchParameter>]

Indicates that the client connects by using HTTPS without validating that a trusted CA signed the server certificate. Do not specify this parameter if you specify

a value of IPMI for the ManagementProtocol parameter.

Do not specify this parameter unless you can establish trust in another way, such as if the remote computer is part of a network that is physically secure and

isolated, or if the remote computer is a trusted host in a Windows Remote Management (WinRM) configuration.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	True (ByPropertyName)
Accept wildcard characters?	false

-SkipCNCheck [<SwitchParameter>]

Indicates that the certificate CN of the server does not need to match the host name of the server. Do not specify this parameter if you specify a value of IPMI

for the ManagementProtocol parameter.

Specify this parameter only for managing devices by using WS-Management over HTTPS. Be sure to specify this parameter only for trusted computers.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	True (ByPropertyName)

Accept wildcard characters? false

`-SkipRevocationCheck [<SwitchParameter>]`

Indicates that the cmdlet skips the revocation check of server certificates. Do not specify this parameter if you specify a value of IPMI for the

ManagementProtocol parameter.

Be sure to specify this parameter only for trusted computers.

Required? false

Position? named

Default value False

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

`-TargetAddress <String>`

Specifies the name or IP address of the management port on the remote hardware device. For server hardware, this is typically a dedicated Baseboard Management

Controller (BMC) IP address. For other devices, like network switches, this is the IP address of their management port.

For desktop and mobile devices, the BMC

sometimes shares the same IP address as the computer.

Required? true

Position? 1

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

`-ThrottleLimit <Int32>`

Specifies the maximum number of concurrent operations that can be established to run the cmdlet. If this parameter is omitted or a value of `0` is entered, then

Windows PowerShell calculates an optimum throttle limit for the cmdlet based on the number of CIM cmdlets that are running on the computer. The throttle limit

applies only to the current cmdlet, not to the session or to the computer.

Required?	false
Position?	named
Default value	None
Accept pipeline input?	False
Accept wildcard characters?	false

-TimeoutSec <UInt32>

Specifies how long to wait, in seconds, for a response from the remote hardware device. After this period, the cmdlet abandons the connection attempt.

Required?	false
Position?	named
Default value	None
Accept pipeline input?	True (ByPropertyName)
Accept wildcard characters?	false

-UseSSL [<SwitchParameter>]

Indicates that the server connects to the target computer by using SSL. WSMAN encrypts all content transmitted over the network. Specify this parameter to use the additional protection of HTTPS instead of HTTP. If you specify this parameter and SSL is not available on the connection port, the command fails.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	True (ByPropertyName)
Accept wildcard characters?	false

-WhatIf [<SwitchParameter>]

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

System.String

System.Management.Automation.PSCredential

Microsoft.PowerShell.Cmdletization.GeneratedTypes.PcsvDevice.ManagementProtocol

System.UInt16

Microsoft.PowerShell.Cmdletization.GeneratedTypes.PcsvDevice.Authentication

System.Management.Automation.SwitchParameter

System.UInt32

Microsoft.Management.Infrastructure.CimInstance[]

OUTPUTS

Microsoft.Management.Infrastructure.CimInstance

Microsoft.Management.Infrastructure.CimInstance#root/Microsoft/Windows/HardwareManagement/MSFT_PCSVDevice

The cmdlet only returns an MSFT_PCSVDevice object if you specify the PassThru parameter.

NOTES

----- Example 1: Shut down a computer -----

```
PS C:\> $Credential = Get-Credential
```

```
PS C:\> Stop-PcsvDevice -TargetAddress "10.1.12.43" -Credential $Credential -ManagementProtocol IPMI
```

This example shuts down a computer.

The first command uses the Get-Credential cmdlet to create a credential, and then stores it in the \$Credential variable. The cmdlet prompts you for a user name and password. For more information, type ``Get-Help Get-Credential``.

The second command shuts down the computer that has the management IP address 10.1.12.43 by using the IPMI management protocol. The command specifies the credential object, stored in the \$Credential variable, needed to connect to the computer. By default, the cmdlet prompts you before it stops the remote hardware device.

RELATED LINKS

Online

Version:

https://learn.microsoft.com/powershell/module/pcsvdevice/stop-pcsvdevice?view=windowsserver2022-ps&wt.mc_id=ps-gethelp

Get-PcsvDevice

Restart-PcsvDevice

Set-PcsvDeviceBootConfiguration

Start-PcsvDevice