



Windows PowerShell Get-Help on Cmdlet 'Test-AzSentinelDataConnectorCheckRequirement'

PS:\>Get-HELP Test-AzSentinelDataConnectorCheckRequirement -Full

NAME

Test-AzSentinelDataConnectorCheckRequirement

SYNOPSIS

Get requirements state for a data connector type.

SYNTAX

```
Test-AzSentinelDataConnectorCheckRequirement -ResourceGroupName <String> -WorkspaceName <String>
[-SubscriptionId <String>] -Kind <DataConnectorKind> [-TenantId
<String>] [-DefaultProfile <PSObject>] [-AsJob] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend
<SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>]
[-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]
```

```
Test-AzSentinelDataConnectorCheckRequirement -ResourceGroupName <String> -WorkspaceName <String>
[-SubscriptionId <String>] -Kind <DataConnectorKind>
-ASCSubscriptionId <String> [-DefaultProfile <PSObject>] [-AsJob] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>]
[-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait]
[-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm]
[<CommonParameters>]
```

DESCRIPTION

Get requirements state for a data connector type.

PARAMETERS

-ResourceGroupName <String>

The Resource Group Name.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-WorkspaceName <String>

[Alias('DataConnectionName')]

The name of the workspace.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

Gets subscription credentials which uniquely identify Microsoft Azure subscription.

The subscription ID forms part of the URI for every service call.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Kind <DataConnectorKind>

Kind of the the data connection

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-TenantId <String>

The TenantId.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ASCSubscriptionId <String>

ASC Subscription Id.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

[Parameter(ParameterSetName = 'AmazonWebServicesCloudTrail', Mandatory)]

[Parameter(ParameterSetName = 'AmazonWebServicesS3', Mandatory)]

[Parameter(ParameterSetName = 'GenericUI', Mandatory)]

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-AsJob [<SwitchParameter>]

Run the command as a job

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-NoWait [<SwitchParameter>]

Run the command asynchronously

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug,

ErrorAction, ErrorVariable, WarningAction, WarningVariable,
OutBuffer, PipelineVariable, and OutVariable. For more information, see
about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.SecurityInsights.Models.Api20210901Preview.DataConnectorsCheckRequirements

----- EXAMPLE 1 -----

```
PS C:\>Test-AzSentinelDataConnectorCheckRequirement -ResourceGroupName "myResourceGroupName"  
-WorkspaceName "myWorkspaceName" -Kind "APIPolling"
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.securityinsights/test-azsentineldataconnectorcheckrequirement>