



Windows PowerShell Get-Help on Cmdlet 'Undo-AzKeyVaultManagedStorageSasDefinitionRemoval'

PS:\>Get-HELP Undo-AzKeyVaultManagedStorageSasDefinitionRemoval -Full

NAME

Undo-AzKeyVaultManagedStorageSasDefinitionRemoval

SYNOPSIS

Recovers a previously deleted KeyVault-managed storage SAS definition.

SYNTAX

```
Undo-AzKeyVaultManagedStorageSasDefinitionRemoval [-InputObject]
<Microsoft.Azure.Commands.KeyVault.Models.PSDeletedKeyVaultManagedStorageSasDefinitionIdentityItem>
[-AccountName] <System.String> [-DefaultProfile]
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer> [-Confirm] [-WhatIf]
[<CommonParameters>]
```

```
Undo-AzKeyVaultManagedStorageSasDefinitionRemoval [-VaultName] <System.String> [-AccountName]
<System.String> [-Name] <System.String> [-DefaultProfile]
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer> [-Confirm] [-WhatIf]
[<CommonParameters>]
```

DESCRIPTION

The `Undo-AzKeyVaultManagedStorageSasDefinitionRemoval` command recovers a previously deleted managed storage SAS definition, provided that soft delete is enabled for this vault, and that the attempt to recover occurs during the recovery interval.

PARAMETERS

`-AccountName` <System.String>

KeyVault-managed storage account name. Cmdlet constructs the FQDN of a managed storage SAS definition from vault name, currently-selected environment and managed storage account name.

Required? true

Position? 1

Default value None

Accept pipeline input? False

Accept wildcard characters? false

`-DefaultProfile` <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-InputObject

<Microsoft.Azure.Commands.KeyVault.Models.PSDeletedKeyVaultManagedStorageSasDefinitionIdentityItem>

Deleted managed storage SAS definition object

Required? true

Position? 0

Default value None
Accept pipeline input? True (ByValue)
Accept wildcard characters? false

-Name <System.String>

Name of the KeyVault-managed storage SAS definition. Cmdlet constructs the FQDN of the target from vault name, currently-selected environment, the name of the managed storage account and the name of the SAS definition.

Required? true
Position? 2
Default value None
Accept pipeline input? False
Accept wildcard characters? false

-VaultName <System.String>

Vault name. Cmdlet constructs the FQDN of a vault based on the name and currently selected environment.

Required? true
Position? 0
Default value None
Accept pipeline input? False
Accept wildcard characters? false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required? false
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.Commands.KeyVault.Models.PSDeletedKeyVaultManagedStorageSasDefinitionIdentityItem

OUTPUTS

Microsoft.Azure.Commands.KeyVault.Models.PSKeyVaultManagedStorageSasDefinition

NOTES

----- Example 1 -----

-InRemovedState

Undo-AzKeyVaultManagedStorageSasDefinitionRemoval -VaultName myVault -AccountName myAccount -Name mySasName

Id : https://myvault.vault.azure.net:443/storage/myaccount/sas/mysasname

Secret Id : https://myvault.vault.azure.net/secrets/myaccount-mysasname

Vault Name : myVault

AccountName : myAccount

Name : mySasName

Parameter :

Enabled : True

Created : 5/24/2018 9:11:08 PM

Updated : 5/24/2018 9:11:08 PM

Tags :

This sequence of commands determines whether the specified storage SAS definition exists in the vault in a deleted state; the subsequent command recovers the deleted sas definition, bringing it back into an active state.

RELATED LINKS

Online

Version:

<https://learn.microsoft.com/powershell/module/az.keyvault/undo-azkeyvaultmanagedstoragesasdefinitionremoval>

Get-AzKeyVaultManagedStorageSasDefinition

Remove-AzKeyVaultManagedStorageSasDefinition

Set-AzKeyVaultManagedStorageSasDefinition