



## ***Windows PowerShell Get-Help on Cmdlet 'Uninstall-Language'***

***PS:\>Get-HELP Uninstall-Language -Full***

### NAME

Uninstall-Language

### SYNOPSIS

Uninstalls a language from a device.

### SYNTAX

Uninstall-Language [-Language] <String> [-PassThru] [<CommonParameters>]

### DESCRIPTION

Uninstalls a language, including all language components, from a device. This operation runs asynchronously.

### PARAMETERS

-Language <String>

The bcp47 tag of the language to install.

Required?            true

Position? 0  
Default value None  
Accept pipeline input? True (ByValue)  
Accept wildcard characters? false

**-PassThru [<SwitchParameter>]**

If specified, this parameter returns the bcp47 tag of the newly installed language upon successful installation.

Required? false  
Position? named  
Default value False  
Accept pipeline input? False  
Accept wildcard characters? false

**<CommonParameters>**

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about\\_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

**INPUTS**

System.String

**OUTPUTS**

System.Void

System.String

## NOTES

----- Example 1: Remove a language from a device -----

```
Uninstall-Language ja-jp
```

This command removes the Japanese language from the device.

## RELATED LINKS

Online

Version:

<https://learn.microsoft.com/powershell/module/languagepackmanagement/uninstall-language?view=windowsserver2022-ps>

InstallLanguage