



python



PowerShell

FPDF Library
PDF generator

Full credit is given to the above companies including the OS that this PDF file was generated!

PowerShell Get-Help on command 'Unpublish-AppvClientPackage'

PS C:\Users\wahid> Get-Help Unpublish-AppvClientPackage

NAME

Unpublish-AppvClientPackage

SYNOPSIS

Removes the extension points for packages.

SYNTAX

Unpublish-AppvClientPackage [-Name] <String> [[-Version] <String>] [-Global]
[-UserSID <String>] [<CommonParameters>]

Unpublish-AppvClientPackage [-Package] <AppvClientPackage> [-Global] [-UserSID
<String>] [<CommonParameters>]

Unpublish-AppvClientPackage [-PackageId] <Guid> [-VersionId] <Guid> [-Global]
[-UserSID <String>] [<CommonParameters>]

DESCRIPTION

The Unpublish-AppvClientPackage cmdlet removes all the extension points of the specified packages. The package contents remain on the target computer. The

package is still added on the client and the appropriate AppvClientPackage object persists.

The package can be unpublished for the current user or if all users that log on to the target computer.

PARAMETERS

-Global [<SwitchParameter>]

Indicates that the packages are unpublished to all users that log into the targeted computer. Otherwise, the packages are only unpublished to the currently running user.

-Name <String>

Specifies the friendly name of the package given during Sequencing time. This value is obtained from the package manifest.

-Package <AppvClientPackage>

Specifies an App-V package.

-PackageId <Guid>

Specifies a GUID that uniquely identifies the package. It can be found in the package manifest or by opening the package in the Microsoft Application Virtualization (App-V) Sequencer. The package ID is shared by all versions of a package.

-UserSID <String>

Specifies the SID of the intended user, in the form of S-1-2-34-56789012-3456789012-345678901-2345. This cmdlet parameter requires elevated rights to run.

-Version <String>

Specifies the version of an App-V package in one specific lineage. If you

do not specify this parameter, the cmdlet operates on the latest version found.

-VersionId <Guid>

Specifies a GUID that differentiates a package version from other versions, whether older, newer, or of a different lineage. If you do not specify this parameter, the cmdlet operates on the latest version of the package.

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

----- Example 1: Unpublish a version of a package -----

```
PS C:\> Unpublish-AppvClientPackage -Name "MyApp" -Version 3
```

This command unpublishes version 3 of the package named MyApp.

-- Example 2: Unpublish a version of a package for all users --

```
PS C:\> Unpublish-AppvClientPackage -Name "MyApp" -Version 3 -Global
```

This command unpublishes version 3 of the package named MyApp for all users on the computer.

REMARKS

To see the examples, type: "get-help Unpublish-AppvClientPackage -examples".

For more information, type: "get-help Unpublish-AppvClientPackage -detailed".

For technical information, type: "get-help Unpublish-AppvClientPackage -full".

For online help, type: "get-help Unpublish-AppvClientPackage -online"