



python



PowerShell

FPDF Library
PDF generator

Full credit is given to the above companies including the OS that this PDF file was generated!

PowerShell Get-Help on command 'Unregister-UevTemplate'

PS C:\Users\wahid> Get-Help Unregister-UevTemplate

NAME

Unregister-UevTemplate

SYNOPSIS

Unregisters a settings location template from Microsoft User Experience Virtualization (UE-V).

SYNTAX

Unregister-UevTemplate -All [-Confirm] [-WhatIf] [<CommonParameters>]

Unregister-UevTemplate [-ID] <String> [-Confirm] [-WhatIf] [<CommonParameters>]

DESCRIPTION

The Unregister-UevTemplate cmdlet unregisters a settings location template from Microsoft User Experience Virtualization (UE-V). A template defines settings to synchronize between computers. After you unregister a template, UE-V no longer synchronizes those settings. If you try to unregister a template that is not registered, the cmdlet returns an error.

You must have administrative credentials to run this cmdlet.

PARAMETERS

-All [<SwitchParameter>]

Indicates that the cmdlet unregisters all settings location templates.

-Confirm [<SwitchParameter>]

Prompts you for confirmation before running the cmdlet.

-ID <String>

Specifies the ID of a settings location template. The cmdlet unregisters the template that you specify. If you specify an ID for a template that is not registered, the cmdlet returns an error.

-WhatIf [<SwitchParameter>]

Shows what would happen if the cmdlet runs. The cmdlet is not run.

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

----- Example 1: Unregister a template -----

```
PS C:\> Unregister-UevTemplate -TemplateId "MicrosoftCalculator6"
```

This command unregisters a settings location template that has the ID MicrosoftCalculator6.

Example 2: Unregister templates for applications that match a specified string

```
PS C:\> Get-UevTemplate -Application "calc" | Unregister-UevTemplate
```

This command uses the Get-UevTemplate cmdlet to get all the registered settings location templates whose application name contains the specified string, and then passes them to the current cmdlet by using the pipeline operator. The cmdlet unregisters all the templates for applications that contain the string calc.

----- Example 3: Unregister all templates -----

```
PS C:\> Unregister-UevTemplate -All
```

This command unregisters all the settings location templates that are currently registered with UE-V.

REMARKS

To see the examples, type: "get-help Unregister-UevTemplate -examples".

For more information, type: "get-help Unregister-UevTemplate -detailed".

For technical information, type: "get-help Unregister-UevTemplate -full".

For online help, type: "get-help Unregister-UevTemplate -online"