



Windows PowerShell Get-Help on Cmdlet 'Update-AzActivityLogAlert'

PS:\>Get-HELP Update-AzActivityLogAlert -Full

NAME

Update-AzActivityLogAlert

SYNOPSIS

Updates 'tags' and 'enabled' fields in an existing Alert rule.

This method is used to update the Alert rule tags, and to enable or disable the Alert rule.

To update other fields use CreateOrUpdate operation.

SYNTAX

Update-AzActivityLogAlert -Name <String> -ResourceGroupName <String> [-SubscriptionId <String>] [-Enabled <Boolean>] [-Tag <Hashtable>] [-DefaultProfile <PSObject>]

[-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]

[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

Update-AzActivityLogAlert -InputObject <IActivityLogAlertIdentity> [-Enabled <Boolean>] [-Tag <Hashtable>] [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend

<SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm]

DESCRIPTION

Updates 'tags' and 'enabled' fields in an existing Alert rule.

This method is used to update the Alert rule tags, and to enable or disable the Alert rule.

To update other fields use CreateOrUpdate operation.

PARAMETERS

-Name <String>

The name of the Activity Log Alert rule.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

The ID of the target subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <IActivityLogAlertIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-Enabled <Boolean>

Indicates whether this Activity Log Alert rule is enabled.

If an Activity Log Alert rule is not enabled, then none of its actions will be activated.

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Tag <Hashtable>

The resource tags

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.Monitor.ActivityLogAlert.Models.IActivityLogAlertIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.Monitor.ActivityLogAlert.Models.Api20201001.IActivityLogAlertResource

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about_Hash_Tables.

INPUTOBJECT <IActivityLogAlertIdentity>: Identity Parameter

[ActivityLogAlertName <String>]: The name of the Activity Log Alert rule.

[Id <String>]: Resource identity path

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[SubscriptionId <String>]: The ID of the target subscription.

----- EXAMPLE 1 -----

```
PS C:\>Update-AzActivityLogAlert -ResourceGroupName $ResourceGroupName -Name $AlertName -Tag
@{"key"="val"} -Enabled $false
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.monitor/update-azactivitylogalert>