



Windows PowerShell Get-Help on Cmdlet 'Update-AzApplicationInsightsWorkbookTemplate'

PS:\>Get-HELP Update-AzApplicationInsightsWorkbookTemplate -Full

NAME

Update-AzApplicationInsightsWorkbookTemplate

SYNOPSIS

Updates a workbook template that has already been added.

SYNTAX

Update-AzApplicationInsightsWorkbookTemplate -Name <String> -ResourceGroupName <String> [-SubscriptionId <String>] [-Author <String>] [-Gallery

<IWorkbookTemplateGallery[]>] [-Localized <Hashtable>] [-Priority <Int32>] [-Tag <Hashtable>] [-TemplateData <Hashtable>] [-DefaultProfile <PSObject>] [-Break]

[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]

[-WhatIf] [-Confirm] [<CommonParameters>]

Update-AzApplicationInsightsWorkbookTemplate -InputObject <IApplicationInsightsIdentity> [-Author <String>] [-Gallery <IWorkbookTemplateGallery[]>] [-Localized

<Hashtable>] [-Priority <Int32>] [-Tag <Hashtable>] [-TemplateData <Hashtable>] [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>]

[-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION

Updates a workbook template that has already been added.

PARAMETERS

-Name <String>

The name of the Application Insights component resource.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

The ID of the target subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <IApplicationInsightsIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-Author <String>

Information about the author of the workbook template.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Gallery <IWorkbookTemplateGallery[]>

Workbook galleries supported by the template.

To construct, see NOTES section for GALLERY properties and create a hash table.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Localized <Hashtable>

Key value pair of localized gallery.

Each key is the locale code of languages supported by the Azure portal.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Priority <Int32>

Priority of the template.

Determines which template to open when a workbook gallery is opened in viewer mode.

Required? false

Position? named

Default value 0

Accept pipeline input? false

Accept wildcard characters? false

-Tag <Hashtable>

Resource tags

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-TemplateData <Hashtable>

Valid JSON object containing workbook template payload.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false
Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.ApplicationInsights.Models.IApplicationInsightsIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.ApplicationInsights.Models.Api20201120.IWorkbookTemplate

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help about_Hash_Tables.

GALLERY <IWorkbookTemplateGallery[]>: Workbook galleries supported by the template.

[Category <String>]: Category for the gallery.

[Name <String>]: Name of the workbook template in the gallery.

[Order <Int32?>]: Order of the template within the gallery.

[ResourceType <String>]: Azure resource type supported by the gallery.

[Type <String>]: Type of workbook supported by the workbook template.

INPUTOBJECT <IApplicationInsightsIdentity>: Identity Parameter

[AnnotationId <String>]: The unique annotation ID. This is unique within a Application Insights component.

[ComponentName <String>]: The name of the Application Insights component resource.

[ExportId <String>]: The Continuous Export configuration ID. This is unique within a Application Insights component.

[Id <String>]: Resource identity path

[KeyId <String>]: The API Key ID. This is unique within a Application Insights component.

[Purgeld <String>]: In a purge status request, this is the Id of the operation the status of which is returned.

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[ResourceName <String>]: The name of the Application Insights component resource.

[RevisionId <String>]: The id of the workbook's revision.

[StorageType <StorageType?>]: The type of the Application Insights component data source for the linked storage account.

[SubscriptionId <String>]: The ID of the target subscription.

[WebTestName <String>]: The name of the Application Insights WebTest resource.

----- EXAMPLE 1 -----

```
PS C:\>Update-AzApplicationInsightsWorkbookTemplate -ResourceGroupName resourceGroup -Name
workbooktemplate-pwsh01 -Tag @{k1='v1'}
```

----- EXAMPLE 2 -----

```
PS C:\>Get-AzApplicationInsightsWorkbookTemplate -ResourceGroupName resourceGroup -Name
workbooktemplate-pwsh01 | Update-AzApplicationInsightsWorkbookTemplate -Tag
@{k1='v1'}
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.applicationinsights/update-azapplicationinsightsworkbooktemplate>