



Windows PowerShell Get-Help on Cmdlet 'Update-AzContainerGroup'

PS:\>Get-HELP Update-AzContainerGroup -Full

NAME

Update-AzContainerGroup

SYNOPSIS

Updates container group tags with specified values.

SYNTAX

Update-AzContainerGroup -Name <String> -ResourceGroupName <String> [-SubscriptionId <String>] [-Location <String>] [-Tag <Hashtable>] [-Zone <String[]>]

[-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

Update-AzContainerGroup -InputObject <IContainerInstanceIdentity> [-Location <String>] [-Tag <Hashtable>] [-Zone <String[]>] [-DefaultProfile <PSObject>] [-Break]

[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]

[-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION

Updates container group tags with specified values.

PARAMETERS

-Name <String>

The name of the container group.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

Subscription credentials which uniquely identify Microsoft Azure subscription.

The subscription ID forms part of the URI for every service call.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <IContainerInstanceIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-Location <String>

The resource location.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Tag <Hashtable>

The resource tags.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Zone <String[]>

The zones for the container group.

Required? false

Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.
Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false
Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.ContainerInstance.Models.IContainerInstanceIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.ContainerInstance.Models.Api20221001Preview.IContainerGroup

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help about_Hash_Tables.

INPUTOBJECT <IContainerInstanceIdentity>: Identity Parameter

[ContainerGroupName <String>]: The name of the container group.

[ContainerName <String>]: The name of the container instance.

[Id <String>]: Resource identity path

[Location <String>]: The identifier for the physical azure location.

[ResourceGroupName <String>]: The name of the resource group.

[SubnetName <String>]: The name of the subnet.

[SubscriptionId <String>]: Subscription credentials which uniquely identify Microsoft Azure subscription. The subscription ID forms part of the URI for every service call.

[VirtualNetworkName <String>]: The name of the virtual network.

----- EXAMPLE 1 -----

```
PS C:\>$container = Update-AzContainerGroup -Name test-cg -ResourceGroupName test-rg -Tag @{"k"="v"}
```

```
$container.Tag | Format-List
```

----- EXAMPLE 2 -----

```
PS C:\>$container = Get-AzContainerGroup -Name test-cg -ResourceGroupName test-rg | Update-AzContainerGroup
```

```
-Tag @"k=v"
```

```
$container.Tag | Format-List
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.containerinstance/update-azcontainergroup>