



Windows PowerShell Get-Help on Cmdlet 'Update-AzContainerRegistryToken'

PS:\>Get-HELP Update-AzContainerRegistryToken -Full

NAME

Update-AzContainerRegistryToken

SYNOPSIS

Updates a token with the specified parameters.

SYNTAX

```
Update-AzContainerRegistryToken -Name <String> -RegistryName <String> -ResourceGroupName <String>
[-SubscriptionId <String>] [-CredentialsCertificate
<ITokenCertificate[]>] [-CredentialsPassword <ITokenPassword[]>] [-ScopeMapId <String>] [-Status <TokenStatus>]
[-DefaultProfile <PSObject>] [-AsJob] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>]
[-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]
```

```
Update-AzContainerRegistryToken -InputObject <IContainerRegistryIdentity> [-CredentialsCertificate
<ITokenCertificate[]>] [-CredentialsPassword <ITokenPassword[]>]
[-ScopeMapId <String>] [-Status <TokenStatus>] [-DefaultProfile <PSObject>] [-AsJob] [-Break] [-HttpPipelineAppend
<SendAsyncStep[]>] [-HttpPipelinePrepend
```

<SendAsyncStep[]> [-NoWait] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION

Updates a token with the specified parameters.

PARAMETERS

-Name <String>

The name of the token.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-RegistryName <String>

The name of the container registry.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

The ID of the target subscription.

The value must be an UUID.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <IContainerRegistryIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-CredentialsCertificate <ITokenCertificate[]>

.

To construct, see NOTES section for CREDENTIALSCERTIFICATE properties and create a hash table.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-CredentialsPassword <ITokenPassword[]>

.

To construct, see NOTES section for CREDENTIALSPASSWORD properties and create a hash table.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ScopeMapId <String>

The resource ID of the scope map to which the token will be associated with.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Status <TokenStatus>

The status of the token example enabled or disabled.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-AsJob [<SwitchParameter>]

Run the command as a job

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-NoWait [<SwitchParameter>]

Run the command asynchronously

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.ContainerRegistry.Models.IContainerRegistryIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.ContainerRegistry.Models.Api202301Preview.IToken

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about_Hash_Tables.

CREDENTIALSCERTIFICATE <ITokenCertificate[]>: .

[EncodedPemCertificate <String>]: Base 64 encoded string of the public certificate1 in PEM format that will be used for authenticating the token.

[Expiry <DateTime?>]: The expiry datetime of the certificate.

[Name <TokenCertificateName?>]:

[Thumbprint <String>]: The thumbprint of the certificate.

CREDENTIALSPASSWORD <ITokenPassword[]>: .

[CreationTime <DateTime?>]: The creation datetime of the password.

[Expiry <DateTime?>]: The expiry datetime of the password.

[Name <TokenPasswordName?>]: The password name "password1" or "password2"

INPUTOBJECT <IContainerRegistryIdentity>: Identity Parameter

[AgentPoolName <String>]: The name of the agent pool.

[CacheRuleName <String>]: The name of the cache rule.

[ConnectedRegistryName <String>]: The name of the connected registry.

[CredentialSetName <String>]: The name of the credential set.

[ExportPipelineName <String>]: The name of the export pipeline.

[GroupName <String>]: The name of the private link resource.

[Id <String>]: Resource identity path

[ImportPipelineName <String>]: The name of the import pipeline.

[PipelineRunName <String>]: The name of the pipeline run.

[PrivateEndpointConnectionName <String>]: The name of the private endpoint connection.

[RegistryName <String>]: The name of the container registry.

[ReplicationName <String>]: The name of the replication.

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[RunId <String>]: The run ID.

[ScopeMapName <String>]: The name of the scope map.

[SubscriptionId <String>]: The ID of the target subscription. The value must be an UUID.

[TaskName <String>]: The name of the container registry task.

[TaskRunName <String>]: The name of the task run.

[TokenName <String>]: The name of the token.

[WebhookName <String>]: The name of the webhook.

----- EXAMPLE 1 -----

```
PS C:\>Update-AzContainerRegistryToken -name token -ScopeMapId
```

```
/subscriptions/${subscription}/resourceGroups/myResourceGroups/providers/Microsoft.ContainerRegistry/registry/MyRegistries/scopeMaps/test -RegistryName MyRegistry  
-ResourceGroupName myResourceGroups
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.containerregistry/update-azcontainerregistrytoken>