



Windows PowerShell Get-Help on Cmdlet 'Update-AzDevCenterAdminNetworkConnection'

PS: \>Get-HELP Update-AzDevCenterAdminNetworkConnection -Full

WARNING: The names of some imported commands from the module 'Az.DevCenterdata.custom' include unapproved verbs that might make them less discoverable. To find the commands with unapproved verbs, run the Import-Module command again with the Verbose parameter. For a list of approved verbs, type Get-Verb.

NAME

Update-AzDevCenterAdminNetworkConnection

SYNOPSIS

Partially updates a Network Connection

SYNTAX

```
Update-AzDevCenterAdminNetworkConnection -Name <String> -ResourceGroupName <String> [-SubscriptionId
<String>] [-DomainName <String>] [-DomainPassword <String>]
[-DomainUsername <String>] [-OrganizationUnit <String>] [-SubnetId <String>] [-Tag <Hashtable>] [-DefaultProfile
<PSObject>] [-AsJob] [-Break] [-HttpPipelineAppend
<SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>] [-ProxyCredential
<PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf]
[-Confirm] [<CommonParameters>]
```

```

Update-AzDevCenterAdminNetworkConnection -InputObject <IDevCenterIdentity> [-DomainName <String>]
[-DomainPassword <String>] [-DomainUsername <String>]
[-OrganizationUnit <String>] [-SubnetId <String>] [-Tag <Hashtable>] [-DefaultProfile <PSObject>] [-AsJob] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>]
[-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm]
[<CommonParameters>]

```

DESCRIPTION

Partially updates a Network Connection

PARAMETERS

-Name <String>

Name of the Network Connection that can be applied to a Pool.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

The ID of the target subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <IDevCenterIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-DomainName <String>

Active Directory domain name

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DomainPassword <String>

The password for the account used to join domain

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DomainUsername <String>

The username of an Active Directory account (user or service account) that has permissions to create computer objects in Active Directory.

Required format: admin@contoso.com.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-OrganizationUnit <String>

Active Directory domain Organization Unit (OU)

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubnetId <String>

The subnet to attach Virtual Machines to

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Tag <Hashtable>

Resource tags.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-AsJob [<SwitchParameter>]

Run the command as a job

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-NoWait [<SwitchParameter>]

Run the command asynchronously

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.DevCenter.Models.IDevCenterIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.DevCenter.Models.Api20231001Preview.INetworkConnection

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

[about_Hash_Tables](#).

INPUTOBJECT <IDevCenterIdentity>: Identity Parameter

[AttachedNetworkConnectionName <String>]: The name of the attached NetworkConnection.

[CatalogName <String>]: The name of the Catalog.

[DevBoxDefinitionName <String>]: The name of the Dev Box definition.

[DevCenterName <String>]: The name of the devcenter.

[EnvironmentDefinitionName <String>]: The name of the Environment Definition.

[EnvironmentTypeName <String>]: The name of the environment type.

[GalleryName <String>]: The name of the gallery.

[Id <String>]: Resource identity path

[ImageName <String>]: The name of the image.

[Location <String>]: The Azure region

[NetworkConnectionName <String>]: Name of the Network Connection that can be applied to a Pool.

[OperationId <String>]: The ID of an ongoing async operation

[PoolName <String>]: Name of the pool.

[ProjectName <String>]: The name of the project.

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[ScheduleName <String>]: The name of the schedule that uniquely identifies it.

[SubscriptionId <String>]: The ID of the target subscription.

[TaskName <String>]: The name of the Task.

[VersionName <String>]: The version of the image.

----- EXAMPLE 1 -----

```
PS C:\>Update-AzDevCenterAdminNetworkConnection -Name eastusNetwork -ResourceGroupName testRg -SubnetId  
"/subscriptions/00000000-0000-0000-0000-000000000000/resourceGroups/ExampleRG/providers/Microsoft.Network/virtual  
Networks/ExampleVNet/subnets/default" -DomainPassword  
$null
```

----- EXAMPLE 2 -----

```

PS C:\>Update-AzDevCenterAdminNetworkConnection -Name eastusNetwork -ResourceGroupName testRg
-DomainName mydomaincontroller.local -DomainUsername
testuser@mydomaincontroller.local -SubnetId

"/subscriptions/00000000-0000-0000-0000-000000000000/resourceGroups/ExampleRG/providers/Microsoft.Network/virtual
Networks/ExampleVNet/subnets/default"

```

----- EXAMPLE 3 -----

```

PS C:\>$networkConnectionInput = Get-AzDevCenterAdminNetworkConnection -ResourceGroupName testRg -Name
eastusNetwork

Update-AzDevCenterAdminNetworkConnection -InputObject $networkConnectionInput -SubnetId

"/subscriptions/00000000-0000-0000-0000-000000000000/resourceGroups/ExampleRG/providers/Microsoft.Network/virtual
Networks/ExampleVNet/subnets/default" -DomainPassword

$null

```

----- EXAMPLE 4 -----

```

PS C:\>$hybridNetworkConnectionInput = Get-AzDevCenterAdminNetworkConnection -ResourceGroupName testRg
-Name eastusNetwork

```

mydomaincontroller.local -DomainUsername

testuser@mydomaincontroller.local -SubnetId

"/subscriptions/00000000-0000-0000-0000-000000000000/resourceGroups/ExampleRG/providers/Microsoft.Network/virtual
Networks/ExampleVNet/subnets/default"

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.devcenter/update-azdevcenteradminnetworkconnection>