



## ***Windows PowerShell Get-Help on Cmdlet 'Update-AzHealthcareApisService'***

***PS:\>Get-HELP Update-AzHealthcareApisService -Full***

### NAME

Update-AzHealthcareApisService

### SYNOPSIS

Update the metadata of a service instance.

### SYNTAX

Update-AzHealthcareApisService -Name <String> -ResourceGroupName <String> [-SubscriptionId <String>]  
[-PublicNetworkAccess <PublicNetworkAccess>] [-Tag <Hashtable>]

[-DefaultProfile <PSObject>] [-AsJob] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend  
<SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>]

[-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

Update-AzHealthcareApisService -InputObject <IHealthcareApisIdentity> [-PublicNetworkAccess  
<PublicNetworkAccess>] [-Tag <Hashtable>] [-DefaultProfile <PSObject>]

[-AsJob] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait]  
[-Proxy <Uri>] [-ProxyCredential <PSCredential>]

[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

## DESCRIPTION

Update the metadata of a service instance.

## PARAMETERS

-Name <String>

The name of the service instance.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group that contains the service instance.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

The subscription identifier.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -InputObject <IHealthcareApisIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

#### -PublicNetworkAccess <PublicNetworkAccess>

Control permission for data plane traffic coming from public networks while private endpoint is enabled.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -Tag <Hashtable>

Instance tags

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position?            named  
Default value  
Accept pipeline input?    false  
Accept wildcard characters? false

**-AsJob [<SwitchParameter>]**

Run the command as a job

Required?            false  
Position?            named  
Default value        False  
Accept pipeline input?    false  
Accept wildcard characters? false

**-Break [<SwitchParameter>]**

Wait for .NET debugger to attach

Required?            false  
Position?            named  
Default value        False  
Accept pipeline input?    false  
Accept wildcard characters? false

**-HttpPipelineAppend <SendAsyncStep[]>**

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required?            false  
Position?            named  
Default value  
Accept pipeline input?    false  
Accept wildcard characters? false

**-HttpPipelinePrepend <SendAsyncStep[]>**

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-NoWait [<SwitchParameter>]

Run the command asynchronously

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

#### -WhatIf [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -Confirm [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### <CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about\_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

## INPUTS

Microsoft.Azure.PowerShell.Cmdlets.HealthcareApis.Models.IHealthcareApisIdentity

## OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.HealthcareApis.Models.Api20211101.IServicesDescription

## NOTES

### COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about\_Hash\_Tables.

INPUTOBJECT <IHealthcareApisIdentity>: Identity Parameter

[DicomServiceName <String>]: The name of DICOM Service resource.

[FhirDestinationName <String>]: The name of IoT Connector FHIR destination resource.

[FhirServiceName <String>]: The name of FHIR Service resource.

[GroupName <String>]: The name of the private link resource group.

[Id <String>]: Resource identity path

[IotConnectorName <String>]: The name of IoT Connector resource.

[LocationName <String>]: The location of the operation.

[OperationResultId <String>]: The ID of the operation result to get.

[PrivateEndpointConnectionName <String>]: The name of the private endpoint connection associated with the Azure resource

[ResourceGroupName <String>]: The name of the resource group that contains the service instance.

[ResourceName <String>]: The name of the service instance.

[SubscriptionId <String>]: The subscription identifier.

[WorkspaceName <String>]: The name of workspace resource.

----- EXAMPLE 1 -----

```
PS C:\>Update-AzHealthcareApisService -ResourceGroupName azps_test_group -Name azpsapiservice -Tag  
@{"abc"="123"}
```

----- EXAMPLE 2 -----

```
PS C:\>Get-AzHealthcareApisService -ResourceGroupName azps_test_group -Name azpsapiservice |  
Update-AzHealthcareApisService -Tag @{"abc"="123"}
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.healthcareapis/update-azhealthcareapisservice>