



Windows PowerShell Get-Help on Cmdlet 'Update-AzKustoManagedPrivateEndpoint'

PS:\>Get-HELP Update-AzKustoManagedPrivateEndpoint -Full

NAME

Update-AzKustoManagedPrivateEndpoint

SYNOPSIS

Updates a managed private endpoint.

SYNTAX

```
Update-AzKustoManagedPrivateEndpoint -ClusterName <String> -Name <String> -ResourceGroupName <String>
[-SubscriptionId <String>] [-GroupId <String>]
[-PrivateLinkResourceId <String>] [-PrivateLinkResourceRegion <String>] [-RequestMessage <String>] [-DefaultProfile
<PSObject>] [-AsJob] [-Break] [-HttpPipelineAppend
<SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>] [-ProxyCredential
<PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf]
[-Confirm] [<CommonParameters>]
```

```
Update-AzKustoManagedPrivateEndpoint -ClusterName <String> -Name <String> -ResourceGroupName <String>
[-SubscriptionId <String>] -Parameter <IManagedPrivateEndpoint>
[-DefaultProfile <PSObject>] [-AsJob] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend
<SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>]
```

[-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

Update-AzKustoManagedPrivateEndpoint -InputObject <IKustoIdentity> [-GroupId <String>] [-PrivateLinkResourceId <String>] [-PrivateLinkResourceRegion <String>]

[-RequestMessage <String>] [-DefaultProfile <PSObject>] [-AsJob] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait]

[-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

Update-AzKustoManagedPrivateEndpoint -InputObject <IKustoIdentity> -Parameter <IManagedPrivateEndpoint> [-DefaultProfile <PSObject>] [-AsJob] [-Break]

[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]

[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION

Updates a managed private endpoint.

PARAMETERS

-ClusterName <String>

The name of the Kusto cluster.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Name <String>

The name of the managed private endpoint.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.
The name is case insensitive.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-SubscriptionId <String>

The ID of the target subscription.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-InputObject <IKustoIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true
Position? named
Default value
Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-Parameter <IManagedPrivateEndpoint>

Class representing a managed private endpoint.

To construct, see NOTES section for PARAMETER properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-GroupId <String>

The groupId in which the managed private endpoint is created.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-PrivateLinkResourceId <String>

The ARM resource ID of the resource for which the managed private endpoint is created.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-PrivateLinkResourceRegion <String>

The region of the resource to which the managed private endpoint is created.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-RequestMessage <String>

The user request message.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-AsJob [<SwitchParameter>]

Run the command as a job

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-NoWait [<SwitchParameter>]

Run the command asynchronously

Required? false

Position? named

Default value False
Accept pipeline input? false
Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.Kusto.Models.Api20230815.IManagedPrivateEndpoint

Microsoft.Azure.PowerShell.Cmdlets.Kusto.Models.IKustoIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.Kusto.Models.Api20230815.IManagedPrivateEndpoint

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run `Get-Help about_Hash_Tables`.

INPUTOBJECT <IKustoldentity>: Identity Parameter

[AttachedDatabaseConfigurationName <String>]: The name of the attached database configuration.

[ClusterName <String>]: The name of the Kusto cluster.

[DataConnectionName <String>]: The name of the data connection.

[DatabaseName <String>]: The name of the database in the Kusto cluster.

[Id <String>]: Resource identity path

[Location <String>]: The name of Azure region.

[ManagedPrivateEndpointName <String>]: The name of the managed private endpoint.

[OperationId <String>]: The ID of an ongoing async operation.

[PrincipalAssignmentName <String>]: The name of the Kusto principalAssignment.

[PrivateEndpointConnectionName <String>]: The name of the private endpoint connection.

[PrivateLinkResourceName <String>]: The name of the private link resource.

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[SandboxCustomImageName <String>]: The name of the sandbox custom image.

[ScriptName <String>]: The name of the Kusto database script.

[SubscriptionId <String>]: The ID of the target subscription.

PARAMETER <IManagedPrivateEndpoint>: Class representing a managed private endpoint.

[GroupId <String>]: The groupId in which the managed private endpoint is created.

[PrivateLinkResourceId <String>]: The ARM resource ID of the resource for which the managed private endpoint is created.

[PrivateLinkResourceRegion <String>]: The region of the resource to which the managed private endpoint is created.

[RequestMessage <String>]: The user request message.

[SystemDataCreatedAt <DateTime?>]: The timestamp of resource creation (UTC).

[SystemDataCreatedBy <String>]: The identity that created the resource.

[SystemDataCreatedByType <CreatedByType?>]: The type of identity that created the resource.

[SystemDataLastModifiedAt <DateTime?>]: The timestamp of resource last modification (UTC)

[SystemDataLastModifiedBy <String>]: The identity that last modified the resource.

[SystemDataLastModifiedByType <CreatedByType?>]: The type of identity that last modified the resource.

----- EXAMPLE 1 -----

```
PS C:\>Update-AzKustoManagedPrivateEndpoint -ResourceGroupName "testrg" -ClusterName "mycluster" -Name
"ManagedPrivateEndpointName" -RequestMessage "Please Approve
Managed Private Endpoint Request." -GroupId "blob" -PrivateLinkResourceId
"/subscriptions/12345678-1234-1234-1234-123456789098/resourceGroups/testrg/providers/Microsoft.Storage/storageAcco
unts/storageAccountTest"
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.kusto/update-azkustomanagedprivateendpoint>