



Windows PowerShell Get-Help on Cmdlet 'Update-AzKustoScript'

PS:\>Get-HELP Update-AzKustoScript -Full

NAME

Update-AzKustoScript

SYNOPSIS

Updates a database script.

SYNTAX

```
Update-AzKustoScript -ClusterName <String> -DatabaseName <String> -Name <String> -ResourceGroupName <String>
[-SubscriptionId <String>] [-ContinueOnError]

[-ForceUpdateTag <String>] [-ScriptContent <String>] [-ScriptUrl <String>] [-ScriptUrlSasToken <String>] [-DefaultProfile
<PSObject>] [-AsJob] [-Break]

[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>]
[-ProxyCredential <PSCredential>]

[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]
```

```
Update-AzKustoScript -ClusterName <String> -DatabaseName <String> -Name <String> -ResourceGroupName <String>
[-SubscriptionId <String>] -Parameter <IScript>

[-DefaultProfile <PSObject>] [-AsJob] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend
<SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>]
```

[-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

Update-AzKustoScript -InputObject <IKustoIdentity> [-ContinueOnError] [-ForceUpdateTag <String>] [-ScriptContent
<String>] [-ScriptUrl <String>] [-ScriptUrlSasToken
<String>] [-DefaultProfile <PSObject>] [-AsJob] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend
<SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>]
[-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

Update-AzKustoScript -InputObject <IKustoIdentity> -Parameter <IScript> [-DefaultProfile <PSObject>] [-AsJob] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>]
[-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm]
[<CommonParameters>]

DESCRIPTION

Updates a database script.

PARAMETERS

-ClusterName <String>

The name of the Kusto cluster.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DatabaseName <String>

The name of the database in the Kusto cluster.

Required? true

Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Name <String>

The name of the Kusto database script.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-SubscriptionId <String>

The ID of the target subscription.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-InputObject <IKustoIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-Parameter <IScript>

Class representing a database script.

To construct, see NOTES section for PARAMETER properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-ContinueOnError [<SwitchParameter>]

Flag that indicates whether to continue if one of the command fails.

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-ForceUpdateTag <String>

A unique string.

If changed the script will be applied again.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ScriptContent <String>

The script content.

This property should be used when the script is provide inline and not through file in a SA.

Must not be used together with scriptUrl and scriptUrlSasToken properties.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ScriptUrl <String>

The url to the KQL script blob file.

Must not be used together with scriptContent property

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ScriptUrlSasToken <String>

The SaS token that provide read access to the file which contain the script.

Must be provided when using scriptUrl property.

Required? false
Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-AsJob [<SwitchParameter>]

Run the command as a job

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-NoWait [<SwitchParameter>]

Run the command asynchronously

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.Kusto.Models.Api20230815.IScript

Microsoft.Azure.PowerShell.Cmdlets.Kusto.Models.IKustoIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.Kusto.Models.Api20230815.IScript

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

[about_Hash_Tables](#).

INPUTOBJECT <IKustoIdentity>: Identity Parameter

[AttachedDatabaseConfigurationName <String>]: The name of the attached database configuration.

[ClusterName <String>]: The name of the Kusto cluster.

[DataConnectionName <String>]: The name of the data connection.

[DatabaseName <String>]: The name of the database in the Kusto cluster.

[Id <String>]: Resource identity path

[Location <String>]: The name of Azure region.

[ManagedPrivateEndpointName <String>]: The name of the managed private endpoint.

[OperationId <String>]: The ID of an ongoing async operation.

[PrincipalAssignmentName <String>]: The name of the Kusto principalAssignment.

[PrivateEndpointConnectionName <String>]: The name of the private endpoint connection.

[PrivateLinkResourceName <String>]: The name of the private link resource.

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[SandboxCustomImageName <String>]: The name of the sandbox custom image.

[ScriptName <String>]: The name of the Kusto database script.

[SubscriptionId <String>]: The ID of the target subscription.

PARAMETER <IScript>: Class representing a database script.

[Content <String>]: The script content. This property should be used when the script is provide inline and not through file in a SA. Must not be used together

with scriptUrl and scriptUrlSasToken properties.

[ContinueOnError <Boolean?>]: Flag that indicates whether to continue if one of the command fails.

[ForceUpdateTag <String>]: A unique string. If changed the script will be applied again.

[SystemDataCreatedAt <DateTime?>]: The timestamp of resource creation (UTC).

[SystemDataCreatedBy <String>]: The identity that created the resource.

[SystemDataCreatedByType <CreatedByType?>]: The type of identity that created the resource.

[SystemDataLastModifiedAt <DateTime?>]: The timestamp of resource last modification (UTC)

[SystemDataLastModifiedBy <String>]: The identity that last modified the resource.

[SystemDataLastModifiedByType <CreatedByType?>]: The type of identity that last modified the resource.

[Url <String>]: The url to the KQL script blob file. Must not be used together with scriptContent property

[UrlSasToken <String>]: The SaS token that provide read access to the file which contain the script. Must be provided when using scriptUrl property.

----- EXAMPLE 1 -----

```
PS C:\>Update-AzKustoScript -DatabaseName mykustodatabase -Name newkustoscript -ClusterName
testnewkustocluster -ResourceGroupName testrg -ScriptUrl $BlobSASURL
-ScriptUrlSasToken $BlobSASToken
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.kusto/update-azkustoscript>