



Windows PowerShell Get-Help on Cmdlet 'Update-AzNginxDeployment'

PS:\>Get-HELP Update-AzNginxDeployment -Full

NAME

Update-AzNginxDeployment

SYNOPSIS

Update the NGINX deployment

SYNTAX

```
Update-AzNginxDeployment -Name <String> -ResourceGroupName <String> [-SubscriptionId <String>]
[-EnableDiagnosticsSupport] [-IdentityType <IdentityType>]
[-IdentityUserAssignedIdentity <Hashtable>] [-Location <String>] [-ScalingPropertyCapacity <Int32>] [-SkuName
<String>] [-StorageAccountContainerName <String>]
[-StorageAccountName <String>] [-Tag <Hashtable>] [-UserProfilePreferredEmail <String>] [-DefaultProfile <PSObject>]
[-AsJob] [-Break] [-HttpPipelineAppend
<SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>] [-ProxyCredential
<PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf]
[-Confirm] [<CommonParameters>]
```

```
Update-AzNginxDeployment -InputObject <INginxIdentity> [-EnableDiagnosticsSupport] [-IdentityType <IdentityType>]
[-IdentityUserAssignedIdentity <Hashtable>]
```

[-Location <String>] [-ScalingPropertyCapacity <Int32>] [-SkuName <String>] [-StorageAccountContainerName <String>]
 [-StorageAccountName <String>] [-Tag <Hashtable>]
 [-UserProfilePreferredEmail <String>] [-DefaultProfile <PSObject>] [-AsJob] [-Break] [-HttpPipelineAppend
 <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>]
 [-NoWait] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm]
 [<CommonParameters>]

DESCRIPTION

Update the NGINX deployment

PARAMETERS

-Name <String>

The name of targeted NGINX deployment

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

The ID of the target subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <INginxIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-EnableDiagnosticsSupport [<SwitchParameter>]

.

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-IdentityType <IdentityType>

.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-IdentityUserAssignedIdentity <Hashtable>

Dictionary of <UserIdentityProperties>

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Location <String>

.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ScalingPropertyCapacity <Int32>

.

Required? false

Position? named

Default value 0

Accept pipeline input? false

Accept wildcard characters? false

-SkuName <String>

Name of the SKU.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-StorageAccountContainerName <String>

.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-StorageAccountName <String>

.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Tag <Hashtable>

Dictionary of <string>

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-UserProfilePreferredEmail <String>

The preferred support contact email address of the user used for sending alerts and notification.

Can be an empty string or a valid email address.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-AsJob [<SwitchParameter>]

Run the command as a job

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-NoWait [<SwitchParameter>]

Run the command asynchronously

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.Nginx.Models.INginxIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.Nginx.Models.Api20230401.INginxDeployment

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help about_Hash_Tables.

INPUTOBJECT <INginxIdentity>: Identity Parameter

[CertificateName <String>]: The name of certificate

[ConfigurationName <String>]: The name of configuration, only 'default' is supported value due to the singleton of NGINX conf

[DeploymentName <String>]: The name of targeted NGINX deployment

[Id <String>]: Resource identity path

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[SubscriptionId <String>]: The ID of the target subscription.

----- EXAMPLE 1 -----

```
PS C:\>Update-AzNginxDeployment -Name nginx-test -ResourceGroupName nginx-test-rg -EnableDiagnosticsSupport
```

----- EXAMPLE 2 -----

```
PS C:\>Update-AzNginxDeployment -Name nginx-test -ResourceGroupName nginx-test-rg  
-EnableDiagnosticsSupport:$false
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.nginx/update-aznginxdeployment>