



Windows PowerShell Get-Help on Cmdlet 'Update-AzRecoveryServicesAsrMobilityService'

PS:\>Get-HELP Update-AzRecoveryServicesAsrMobilityService -Full

NAME

Update-AzRecoveryServicesAsrMobilityService

SYNOPSIS

Push mobility service agent updates to protected machines.

SYNTAX

```

Update-AzRecoveryServicesAsrMobilityService [-Account
<Microsoft.Azure.Commands.RecoveryServices.SiteRecovery.ASRRunAsAccount>] [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>]
-ReplicationProtectedItem
<Microsoft.Azure.Commands.RecoveryServices.SiteRecovery.ASRReplicationProtectedItem> [-Confirm] [-WhatIf]
[<CommonParameters>]

```

DESCRIPTION

The Update-AzRecoveryServicesAsrMobilityService cmdlet attempts to push mobility service agent updates to protected machines(if an update is available.)

PARAMETERS

-Account <Microsoft.Azure.Commands.RecoveryServices.SiteRecovery.ASRRunAsAccount>

The run as account ID to be used to push the update. Must be one from the list of run as accounts in the ASR fabric corresponding to machine being updated.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-ReplicationProtectedItem <Microsoft.Azure.Commands.RecoveryServices.SiteRecovery.ASRReplicationProtectedItem>

Azure Site Recovery replication protected item to be updated.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByValue)

Accept wildcard characters? false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.Commands.RecoveryServices.SiteRecovery.ASRReplicationProtectedItem

OUTPUTS

Microsoft.Azure.Commands.RecoveryServices.SiteRecovery.ASRJob

NOTES

----- Example 1 -----

```
Update-AzRecoveryServicesAsrMobilityService -ReplicationProtectedItem $rpi -Account  
$fabric.fabricSpecificDetails.RunAsAccounts[0]
```

Job to track Update Replication Protected Item's Mobility Service Agent.

RELATED LINKS

Online Version:

<https://learn.microsoft.com/powershell/module/az.recoveryservices/update-azrecoveryservicesasrmobilityservice>