



Windows PowerShell Get-Help on Cmdlet 'Update-AzRelayNamespace'

PS:\>Get-HELP Update-AzRelayNamespace -Full

NAME

Update-AzRelayNamespace

SYNOPSIS

Creates or updates a namespace.

Once created, this namespace's resource manifest is immutable.

This operation is idempotent.

SYNTAX

Update-AzRelayNamespace -Name <String> -ResourceGroupName <String> [-SubscriptionId <String>] [-Tag <Hashtable>] [-DefaultProfile <PSObject>] [-Break]

[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]

[-WhatIf] [-Confirm] [<CommonParameters>]

Update-AzRelayNamespace -InputObject <IRelayIdentity> [-Tag <Hashtable>] [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>]

[-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION

Creates or updates a namespace.

Once created, this namespace's resource manifest is immutable.

This operation is idempotent.

PARAMETERS

-Name <String>

The namespace name

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

Name of the Resource group within the Azure subscription.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

Subscription credentials which uniquely identify the Microsoft Azure subscription.

The subscription ID forms part of the URI for every service call.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <IRelayIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-Tag <Hashtable>

Resource tags.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.Relay.Models.IRelayIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.Relay.Models.Api20211101.IRelayNamespace

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

[about_Hash_Tables](#).

INPUTOBJECT <IRelayIdentity>: Identity Parameter

[AuthorizationRuleName <String>]: The authorization rule name.

[HybridConnectionName <String>]: The hybrid connection name.

[Id <String>]: Resource identity path

[NamespaceName <String>]: The namespace name

[PrivateEndpointConnectionName <String>]: The PrivateEndpointConnection name

[PrivateLinkResourceName <String>]: The PrivateLinkResource name

[RelayName <String>]: The relay name.

[ResourceGroupName <String>]: Name of the Resource group within the Azure subscription.

[SubscriptionId <String>]: Subscription credentials which uniquely identify the Microsoft Azure subscription. The subscription ID forms part of the URI for every service call.

PRIVATEENDPOINTCONNECTION <IPrivateEndpointConnection[]>: List of private endpoint connections.

[PrivateEndpointId <String>]: The ARM identifier for Private Endpoint.

[PrivateLinkServiceConnectionStateDescription <String>]: Description of the connection state.

[PrivateLinkServiceConnectionStateStatus <PrivateLinkConnectionStatus?>]: Status of the connection.

[ProvisioningState <EndPointProvisioningState?>]: Provisioning state of the Private Endpoint Connection.

[SystemDataCreatedAt <DateTime?>]: The timestamp of resource creation (UTC).

[SystemDataCreatedBy <String>]: The identity that created the resource.

[SystemDataCreatedByType <CreatedByType?>]: The type of identity that created the resource.

[SystemDataLastModifiedAt <DateTime?>]: The timestamp of resource last modification (UTC)

[SystemDataLastModifiedBy <String>]: The identity that last modified the resource.

[SystemDataLastModifiedByType <CreatedByType?>]: The type of identity that last modified the resource.

----- EXAMPLE 1 -----

```
PS C:\>Update-AzRelayNamespace -ResourceGroupName lucas-relay-rg -Name namespace-pwsh01 -Tag @{'k'='v'}
```

----- EXAMPLE 2 -----

```
PS C:\>Get-AzRelayNamespace -ResourceGroupName lucas-relay-rg -Name namespace-pwsh01 |  
Update-AzRelayNamespace -Tag @{'k'='v'}
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.relay/update-azrelaynamespace>