



Windows PowerShell Get-Help on Cmdlet 'Update-AzResourceGraphQuery'

PS:\>Get-HELP Update-AzResourceGraphQuery -Full

NAME

Update-AzResourceGraphQuery

SYNOPSIS

Updates a graph query that has already been added.

SYNTAX

Update-AzResourceGraphQuery -Name <String> -ResourceGroupName <String> [-SubscriptionId <String>] [-Description <String>] [-Query <String>] [-File <String>] [-Tag

<Hashtable>] [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

Update-AzResourceGraphQuery -InputObject <IResourceGraphIdentity> [-Description <String>] [-Query <String>] [-File <String>] [-Tag <Hashtable>] [-DefaultProfile

<PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]

[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION

Updates a graph query that has already been added.

PARAMETERS

-Name <String>

The name of the Graph Query resource.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

The Azure subscription Id.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <IResourceGraphIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-Description <String>

The description of a graph query.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Query <String>

KQL query that will be graph.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-File <String>

The content of the file will be passed to the query parameter.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Tag <Hashtable>

Resource tags

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.ResourceGraph.Models.Api20180901Preview.IGraphQueryResource

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about_Hash_Tables.

INPUTOBJECT <IResourceGraphIdentity>: Identity Parameter

[Id <String>]: Resource identity path

[ResourceGroupName <String>]: The name of the resource group.

[ResourceName <String>]: The name of the Graph Query resource.

[SubscriptionId <String>]: The Azure subscription Id.

----- EXAMPLE 1 -----

```
PS C:\>Update-AzResourceGraphQuery -ResourceGroupName azure-rg-test -Name query-t05 -Query "project id, name,
type, location, tags" -Tag @{'key1'=1;'key2'=2}
```

----- EXAMPLE 2 -----

```
PS C:\>$query = Get-AzResourceGraphQuery -ResourceGroupName azure-rg-test -Name query-t05
```

```
Update-AzResourceGraphQuery -InputObject $query -File './Query.kql'
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.resourcegraph/update-azresourcegraphquery>