



Windows PowerShell Get-Help on Cmdlet 'Update-AzSecurityConnector'

PS:\>Get-HELP Update-AzSecurityConnector -Full

NAME

Update-AzSecurityConnector

SYNOPSIS

Update a security connector

SYNTAX

```
Update-AzSecurityConnector -Name <String> -ResourceGroupName <String> [-SubscriptionId <String>]
[-EnvironmentData <ISecurityConnectorEnvironment>] [-EnvironmentName
<String>] [-Etag <String>] [-HierarchyIdentifier <String>] [-Kind <String>] [-Location <String>] [-Offering
<ICloudOffering[]>] [-Tag <Hashtable>] [-DefaultProfile
<PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy
<Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]
```

```
Update-AzSecurityConnector -InputObject <ISecurityIdentity> [-EnvironmentData <ISecurityConnectorEnvironment>]
[-EnvironmentName <String>] [-Etag <String>]
[-HierarchyIdentifier <String>] [-Kind <String>] [-Location <String>] [-Offering <ICloudOffering[]>] [-Tag <Hashtable>]
[-DefaultProfile <PSObject>] [-Break]
```

[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]
[-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION

Update a security connector

PARAMETERS

-Name <String>

The security connector name.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group within the user's subscription.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

Azure subscription ID

Required? false

Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-InputObject <ISecurityIdentity>

Identity Parameter

Required? true
Position? named
Default value
Accept pipeline input? true (ByValue)
Accept wildcard characters? false

-EnvironmentData <ISecurityConnectorEnvironment>

The security connector environment data.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-EnvironmentName <String>

The multi cloud resource's cloud name.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Etag <String>

Entity tag is used for comparing two or more entities from the same requested resource.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HierarchyIdentifier <String>

The multi cloud resource identifier (account id in case of AWS connector, project number in case of GCP connector).

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Kind <String>

Kind of the resource

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Location <String>

Location where the resource is stored

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Offering <ICloudOffering[]>

A collection of offerings for the security connector.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Tag <Hashtable>

A list of key value pairs that describe the resource.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters](https://go.microsoft.com/fwlink/?LinkID=113216) (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.Security.Models.ISecurityIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.Security.Models.ISecurityConnector

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run `Get-Help`

`about_Hash_Tables`.

ENVIRONMENTDATA <ISecurityConnectorEnvironment>: The security connector environment data.

EnvironmentType <String>: The type of the environment data.

INPUTOBJECT <ISecurityIdentity>: Identity Parameter

[ApiId <String>]: API revision identifier. Must be unique in the API Management service instance. Non-current revision has ;rev=n as a suffix where n is the revision number.

[GroupFqName <String>]: The GitLab group fully-qualified name.

[Id <String>]: Resource identity path

[OperationResultId <String>]: The operation result Id.

[OrgName <String>]: The Azure DevOps organization name.

[OwnerName <String>]: The GitHub owner name.

[ProjectName <String>]: The project name.

[RepoName <String>]: The repository name.

[ResourceGroupName <String>]: The name of the resource group within the user's subscription. The name is case insensitive.

[SecurityConnectorName <String>]: The security connector name.

[ServiceName <String>]: The name of the API Management service.

[SubscriptionId <String>]: Azure subscription ID

OFFERING <ICloudOffering[]>: A collection of offerings for the security connector.

OfferingType <String>: The type of the security offering.

----- EXAMPLE 1 -----

```
PS C:\>Update-AzSecurityConnector -ResourceGroupName "securityConnectors-pwsh-tmp" -Name  
"ado-sdk-pwsh-test03" -Tag @{myTag="v1"}
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.security/update-azsecurityconnector>