



Windows PowerShell Get-Help on Cmdlet 'Update-AzSecurityConnectorAzureDevOpsOrg'

PS:\>Get-HELP Update-AzSecurityConnectorAzureDevOpsOrg -Full

NAME

Update-AzSecurityConnectorAzureDevOpsOrg

SYNOPSIS

Update monitored Azure DevOps organization details.

SYNTAX

```
Update-AzSecurityConnectorAzureDevOpsOrg -OrgName <String> -ResourceGroupName <String>
-SecurityConnectorName <String> [-SubscriptionId <String>]
[-ActionableRemediation <IActionableRemediation>] [-DefaultProfile <PSObject>] [-AsJob] [-Break] [-HttpPipelineAppend
<SendAsyncStep[]>] [-HttpPipelinePrepend
<SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf]
[-Confirm] [<CommonParameters>]
```

```
Update-AzSecurityConnectorAzureDevOpsOrg -InputObject <ISecurityIdentity> [-ActionableRemediation
<IActionableRemediation>] [-DefaultProfile <PSObject>] [-AsJob]
[-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>]
[-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]
```

DESCRIPTION

Update monitored Azure DevOps organization details.

PARAMETERS

-OrgName <String>

The Azure DevOps organization name.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SecurityConnectorName <String>

The security connector name.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

Azure subscription ID

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <ISecurityIdentity>

Identity Parameter

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-ActionableRemediation <IActionableRemediation>

Configuration payload for PR Annotations.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-AsJob [<SwitchParameter>]

Run the command as a job

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-NoWait [<SwitchParameter>]

Run the command asynchronously

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug,

ErrorAction, ErrorVariable, WarningAction, WarningVariable,

OutBuffer, PipelineVariable, and OutVariable. For more information, see

about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.Security.Models.ISecurityIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.Security.Models.IAzureDevOpsOrg

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about_Hash_Tables.

ACTIONABLEREMEDIATION <IActionableRemediation>: Configuration payload for PR Annotations.

[BranchConfiguration <ITargetBranchConfiguration>]: Repository branch configuration for PR Annotations.

[AnnotateDefaultBranch <String>]: Configuration of PR Annotations on default branch. Enabled - PR Annotations are enabled on the resource's default

branch. Disabled - PR Annotations are disabled on the resource's default branch.

[BranchName <List<String>>]: Gets or sets branches that should have annotations.

[CategoryConfiguration <List<ICategoryConfiguration>>]: Gets or sets list of categories and severity levels.

[Category <String>]: Rule categories. Code - code scanning results. Artifact scanning results. Dependencies scanning results.

IaC results. Secrets scanning results. Container scanning results.

[MinimumSeverityLevel <String>]: Gets or sets minimum severity level for a given category.

[InheritFromParentState <String>]: Update Settings. Enabled - Resource should inherit configurations from parent. Disabled - Resource should

not inherit configurations from parent.

[State <String>]: ActionableRemediation Setting. None - the setting was never set.

ActionableRemediation is enabled. Disabled

- ActionableRemediation is disabled.

INPUTOBJECT <ISecurityIdentity>: Identity Parameter

[Apild <String>]: API revision identifier. Must be unique in the API Management service instance. Non-current revision has ;rev=n as a suffix where n is the revision number.

[GroupFqName <String>]: The GitLab group fully-qualified name.

[Id <String>]: Resource identity path

[OperationResultId <String>]: The operation result Id.

[OrgName <String>]: The Azure DevOps organization name.

[OwnerName <String>]: The GitHub owner name.

[ProjectName <String>]: The project name.

[RepoName <String>]: The repository name.

[ResourceGroupName <String>]: The name of the resource group within the user's subscription. The name is case insensitive.

[SecurityConnectorName <String>]: The security connector name.

[ServiceName <String>]: The name of the API Management service.

[SubscriptionId <String>]: Azure subscription ID

----- EXAMPLE 1 -----

```
PS C:\>$config = New-AzSecurityConnectorActionableRemediationObject -State Enabled -InheritFromParentState Disabled -CategoryConfiguration @( @{category="laC"; minimumSeverityLevel="High"})
```

```
Update-AzSecurityConnectorAzureDevOpsOrg -ResourceGroupName "securityConnectors-pwsh-tmp" -SecurityConnectorName "ado-sdk-pwsh-test03" -OrgName "org1" -ActionableRemediation $config
```


RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.security/update-azsecurityconnectorazuredevopsorg>