



Windows PowerShell Get-Help on Cmdlet 'Update-AzSentinelEntityQuery'

PS:\>Get-HELP Update-AzSentinelEntityQuery -Full

NAME

Update-AzSentinelEntityQuery

SYNOPSIS

Updates the entity query.

SYNTAX

```
Update-AzSentinelEntityQuery -ResourceGroupName <String> -WorkspaceName <String> -EntityQueryId <String>
[-SubscriptionId <String>] [-Title <String>] [-Content
    <String>] [-Description <String>] [-QueryDefinitionQuery <String>] [-InputEntityType <EntityType>]
[-RequiredInputFieldsSet <String[]>] [-EntitiesFilter
    <ActivityEntityQueriesPropertiesEntitiesFilter>] [-TemplateName <String>] [-Enabled] [-Disabled] [-DefaultProfile
    <PSObject>] [-AsJob] [-Break] [-HttpPipelineAppend
    <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>] [-ProxyCredential
    <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf]
    [-Confirm] [<CommonParameters>]
```

```
Update-AzSentinelEntityQuery -InputObject <ISecurityInsightsIdentity> [-Title <String>] [-Content <String>] [-Description
    <String>] [-QueryDefinitionQuery <String>]
```

[-InputEntityType <EntityType>] [-RequiredInputFieldsSet <String[]>] [-EntitiesFilter
 <ActivityEntityQueriesPropertiesEntitiesFilter>] [-TemplateName <String>]
 [-Enabled] [-Disabled] [-DefaultProfile <PSObject>] [-AsJob] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>]
 [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait]
 [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm]
 [<CommonParameters>]

DESCRIPTION

Updates the entity query.

PARAMETERS

-ResourceGroupName <String>

The Resource Group Name.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-WorkspaceName <String>

[Alias('DataConnectionName')]

The name of the workspace.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-EntityQueryId <String>

The Id of the Entity Query.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

Gets subscription credentials which uniquely identify Microsoft Azure subscription.

The subscription ID forms part of the URI for every service call.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <ISecurityInsightsIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-Title <String>

Required? false

Position? named

Default value

Accept pipeline input? false
Accept wildcard characters? false

-Content <String>

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Description <String>

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-QueryDefinitionQuery <String>

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-InputEntityType <EntityType>

Required? false
Position? named
Default value
Accept pipeline input? false

Accept wildcard characters? false

-RequiredInputFieldsSet <String[]>

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-EntitiesFilter <ActivityEntityQueriesPropertiesEntitiesFilter>

To construct, see NOTES section for ENTITIESFILTER properties and create a hash table.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-TemplateName <String>

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Enabled [<SwitchParameter>]

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Disabled [<SwitchParameter>]

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-AsJob [<SwitchParameter>]

Run the command as a job

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-NoWait [<SwitchParameter>]

Run the command asynchronously

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.SecurityInsights.Models.ISecurityInsightsIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.SecurityInsights.Models.Api20210901Preview.CustomEntityQuery

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

[about_Hash_Tables](#).

ENTITIESFILTER <ActivityEntityQueriesPropertiesEntitiesFilter>:

[(Any) <String[]>]: This indicates any property can be added to this object.

INPUTOBJECT <ISecurityInsightsIdentity>: Identity Parameter

[ActionId <String>]: Action ID

[AlertRuleTemplateId <String>]: Alert rule template ID

[AutomationRuleId <String>]: Automation rule ID

[BookmarkId <String>]: Bookmark ID

[ConsentId <String>]: consent ID

[DataConnectorId <String>]: Connector ID

[EntityId <String>]: entity ID

[EntityQueryId <String>]: entity query ID

[EntityQueryTemplateId <String>]: entity query template ID

[Id <String>]: Resource identity path

[IncidentCommentId <String>]: Incident comment ID

[IncidentId <String>]: Incident ID

[MetadataName <String>]: The Metadata name.

[Name <String>]: Threat intelligence indicator name field.

[RelationName <String>]: Relation Name

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[RuleId <String>]: Alert rule ID

[SentinelOnboardingStateName <String>]: The Sentinel onboarding state name. Supports - default

[SettingsName <String>]: The setting name. Supports - Anomalies, EyesOn, EntityAnalytics, Ueba

[SourceControlId <String>]: Source control Id

[SubscriptionId <String>]: The ID of the target subscription.

[WorkspaceName <String>]: The name of the workspace.

----- EXAMPLE 1 -----

```
PS C:\>Update-AzSentinelEntityQuery -ResourceGroupName "myResourceGroupName" -WorkspaceName
"myWorkspaceName" -EntityQueryId "4a21e485-75ae-48b3-a7b9-e6a92bcfe434"
-Title "myEntityQuery Title"
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.securityinsights/update-azsentinelentityquery>