



**Full credit is given to all the above companies including the Operating System that this PDF file was generated!**

### ***Windows PowerShell Get-Help on Cmdlet 'Update-AzSentinelIncidentRelation'***

**PS:\>Get-HELP Update-AzSentinelIncidentRelation -Full**

#### **NAME**

Update-AzSentinelIncidentRelation

#### **SYNOPSIS**

Creates or updates the incident relation.

#### **SYNTAX**

```
Update-AzSentinelIncidentRelation -IncidentId <String> -RelationName <String> -ResourceGroupName <String>
[-SubscriptionId <String>] -WorkspaceName <String>

[-RelatedResourceId <String>] [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>]
[-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>]

[-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]
```

```
Update-AzSentinelIncidentRelation -InputObject <ISecurityInsightsIdentity> [-RelatedResourceId <String>]
[-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend
<SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm]

[<CommonParameters>]
```

## DESCRIPTION

Creates or updates the incident relation.

## PARAMETERS

-IncidentId <String>

    Incident ID

        Required?                 true

        Position?                 named

        Default value

        Accept pipeline input?    false

        Accept wildcard characters? false

-RelationName <String>

    Relation Name

        Required?                 true

        Position?                 named

        Default value

        Accept pipeline input?    false

        Accept wildcard characters? false

-ResourceGroupName <String>

    The name of the resource group.

    The name is case insensitive.

        Required?                 true

        Position?                 named

        Default value

        Accept pipeline input?    false

        Accept wildcard characters? false

-SubscriptionId <String>

The ID of the target subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-WorkspaceName <String>

The name of the workspace.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <ISecurityInsightsIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-RelatedResourceId <String>

The resource ID of the related resource

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

#### -HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about\_CommonParameters (<https://go.microsoft.com/fwlink/?LinkId=113216>).

## INPUTS

Microsoft.Azure.PowerShell.Cmdlets.SecurityInsights.Models.ISecurityInsightsIdentity

## OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.SecurityInsights.Models.Api20210901Preview.IRelation

## NOTES

### COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help about\_Hash\_Tables.

INPUTOBJECT <ISecurityInsightsIdentity>: Identity Parameter

[ActionId <String>]: Action ID

[AlertRuleTemplateId <String>]: Alert rule template ID

[AutomationRuleId <String>]: Automation rule ID

[BookmarkId <String>]: Bookmark ID

[ConsentId <String>]: consent ID

[DataConnectorId <String>]: Connector ID

[EntityId <String>]: entity ID

[EntityQueryId <String>]: entity query ID

[EntityQueryTemplateId <String>]: entity query template ID

[Id <String>]: Resource identity path

[IncidentCommentId <String>]: Incident comment ID

[IncidentId <String>]: Incident ID

[MetadataName <String>]: The Metadata name.

[Name <String>]: Threat intelligence indicator name field.

[RelationName <String>]: Relation Name

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[RuleId <String>]: Alert rule ID

[SentinelOnboardingStateName <String>]: The Sentinel onboarding state name. Supports - default

[SettingsName <String>]: The setting name. Supports - Anomalies, EyesOn, EntityAnalytics, Ueba

[SourceControlId <String>]: Source control Id

[SubscriptionId <String>]: The ID of the target subscription.

[WorkspaceName <String>]: The name of the workspace.

----- EXAMPLE 1 -----

```
PS C:\>$bookmark = Get-AzSentinelBookmark -ResourceGroupName "myResourceGroup" -WorkspaceName  
"myWorkspaceName" -Id "myBookmarkId"
```

```
Update-AzSentinelIncidentRelation -ResourceGroupName "myResourceGroup" -WorkspaceName "myWorkspaceName"  
-IncidentId "myIncidentId" -RelationName ((New-Guid).Guid)  
-RelatedResourceId ($bookmark.Id)
```

## RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.securityinsights/update-azsentinelincidentrelation>