



Windows PowerShell Get-Help on Cmdlet 'Update-AzStorageMoverJobDefinition'

PS:\>Get-HELP Update-AzStorageMoverJobDefinition -Full

NAME

Update-AzStorageMoverJobDefinition

SYNOPSIS

Updates properties for a Job Definition resource.

Properties not specified in the request body will be unchanged.

SYNTAX

```
Update-AzStorageMoverJobDefinition -Name <String> -ProjectName <String> -ResourceGroupName <String>
-StorageMoverName <String> [-SubscriptionId <String>] [-AgentName
    <String>] [-CopyMode <CopyMode>] [-Description <String>] [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend
    <SendAsyncStep[]>] [-HttpPipelinePrepend
    <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm]
    [<CommonParameters>]
```

```
Update-AzStorageMoverJobDefinition -Name <String> -ProjectName <String> -ResourceGroupName <String>
-StorageMoverName <String> [-SubscriptionId <String>]
    -JobDefinition <IJobDefinitionUpdateParameters> [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend
    <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>]
```

[-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm]
[<CommonParameters>]

Update-AzStorageMoverJobDefinition -InputObject <IStorageMoverIdentity> [-AgentName <String>] [-CopyMode
<CopyMode>] [-Description <String>] [-DefaultProfile
<PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy
<Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

Update-AzStorageMoverJobDefinition -InputObject <IStorageMoverIdentity> -JobDefinition
<IJobDefinitionUpdateParameters> [-DefaultProfile <PSObject>] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential
<PSCredential>] [-ProxyUseDefaultCredentials]
[-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION

Updates properties for a Job Definition resource.

Properties not specified in the request body will be unchanged.

PARAMETERS

-Name <String>

The name of the Job Definition resource.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProjectName <String>

The name of the Project resource.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.
The name is case insensitive.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-StorageMoverName <String>

The name of the Storage Mover resource.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-SubscriptionId <String>

The ID of the target subscription.

Required? false
Position? named
Default value
Accept pipeline input? false

Accept wildcard characters? false

-InputObject <IStorageMoverIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-JobDefinition <IJobDefinitionUpdateParameters>

The Job Definition resource.

To construct, see NOTES section for JOBDEFINITION properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-AgentName <String>

Name of the Agent to assign for new Job Runs of this Job Definition.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-CopyMode <CopyMode>

Strategy to use for copy.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Description <String>

A description for the Job Definition.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false
Position? named
Default value False
Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug,
ErrorAction, ErrorVariable, WarningAction, WarningVariable,

OutBuffer, PipelineVariable, and OutVariable. For more information, see
about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.StorageMover.Models.Api20231001.IJobDefinitionUpdateParameters

Microsoft.Azure.PowerShell.Cmdlets.StorageMover.Models.IStorageMoverIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.StorageMover.Models.Api20231001.IJobDefinition

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help
about_Hash_Tables.

INPUTOBJECT <IStorageMoverIdentity>: Identity Parameter

[AgentName <String>]: The name of the Agent resource.

[EndpointName <String>]: The name of the Endpoint resource.

[Id <String>]: Resource identity path

[JobDefinitionName <String>]: The name of the Job Definition resource.

[JobRunName <String>]: The name of the Job Run resource.

[ProjectName <String>]: The name of the Project resource.

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[StorageMoverName <String>]: The name of the Storage Mover resource.

[SubscriptionId <String>]: The ID of the target subscription.

JOBDEFINITION <IJobDefinitionUpdateParameters>: The Job Definition resource.

[AgentName <String>]: Name of the Agent to assign for new Job Runs of this Job Definition.

[CopyMode <CopyMode?>]: Strategy to use for copy.

[Description <String>]: A description for the Job Definition.

----- EXAMPLE 1 -----

```
PS C:\>Update-AzStorageMoverJobDefinition -Name myJob -ProjectName myProject -ResourceGroupName  
myResourceGroup -StorageMoverName myStorageMover -Description "Update  
Description"
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.storage/mover/update-azstoragemoverjobdefinition>