



Windows PowerShell Get-Help on Cmdlet 'Update-AzStorageMoverSmbEndpoint'

PS:\>Get-HELP Update-AzStorageMoverSmbEndpoint -Full

NAME

Update-AzStorageMoverSmbEndpoint

SYNOPSIS

Updates properties for a SMB endpoint resource.

Properties not specified in the request body will be unchanged.

SYNTAX

```
Update-AzStorageMoverSmbEndpoint -Name <String> -ResourceGroupName <String> -StorageMoverName <String>
[-SubscriptionId <String>] [-CredentialsUsernameUri <String>]
[-CredentialsPasswordUri <String>] [-Description <String>] [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend
<SendAsyncStep[]>] [-HttpPipelinePrepend
<SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm]
[<CommonParameters>]
```

```
Update-AzStorageMoverSmbEndpoint -InputObject <IStorageMoverIdentity> [-CredentialsUsernameUri <String>]
[-CredentialsPasswordUri <String>] [-Description <String>]
[-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend
<SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential
```

<PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION

Updates properties for a SMB endpoint resource.

Properties not specified in the request body will be unchanged.

PARAMETERS

-Name <String>

The name of the endpoint resource.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-StorageMoverName <String>

The name of the Storage Mover resource.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

The ID of the target subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <IStorageMoverIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-CredentialsUsernameUri <String>

The secret URI which stores the username.

Use empty string to clean-up existing value.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-CredentialsPasswordUri <String>

The secret URI which stores the password.

Use empty string to clean-up existing value.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Description <String>

A description for the endpoint.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters](https://go.microsoft.com/fwlink/?LinkID=113216) (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.StorageMover.Models.IStorageMoverIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.StorageMover.Models.Api20231001.IEndpoint

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run `Get-Help about_Hash_Tables`.

INPUTOBJECT <IStorageMoverIdentity>: Identity Parameter

[AgentName <String>]: The name of the Agent resource.

[EndpointName <String>]: The name of the Endpoint resource.

[Id <String>]: Resource identity path

[JobDefinitionName <String>]: The name of the Job Definition resource.

[JobRunName <String>]: The name of the Job Run resource.

[ProjectName <String>]: The name of the Project resource.

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[StorageMoverName <String>]: The name of the Storage Mover resource.

[SubscriptionId <String>]: The ID of the target subscription.

----- EXAMPLE 1 -----

```
PS C:\>Update-AzStorageMoverSmbEndpoint -Name "myendpoint" -ResourceGroupName "myresourcegroup"
-StorageMoverName "mystoragemover" -CredentialsUsernameUri
        "https://examples-azureKeyVault.vault.azure.net/secrets/username2" -CredentialsPasswordUri
"https://examples-azureKeyVault.vault.azure.net/secrets/password2"
-Description "update endpoint"
```

----- EXAMPLE 2 -----

```
PS C:\>Get-AzStorageMoverEndpoint -ResourceGroupName "myresourcegroup" -StorageMoverName
"mystoragemover" -Name "myendpoint" | Update-AzStorageMoverSmbEndpoint
-CredentialsPasswordUri "" -CredentialsUsernameUri "" -Description "update endpoint again"
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.storage/mover/update-azstoragemoversmbendpoint>