



Windows PowerShell Get-Help on Cmdlet 'Update-AzWvdApplication'

PS:\>Get-HELP Update-AzWvdApplication -Full

NAME

Update-AzWvdApplication

SYNOPSIS

Update an application.

SYNTAX

Update-AzWvdApplication -GroupName <String> -Name <String> -ResourceGroupName <String> [-SubscriptionId <String>] [-ApplicationType <RemoteApplicationType>]

[-CommandLineArgument <String>] [-CommandLineSetting <CommandLineSetting>] [-Description <String>] [-FilePath <String>] [-FriendlyName <String>] [-IconIndex <Int32>]

[-IconPath <String>] [-MsixPackageApplicationId <String>] [-MsixPackageFamilyName <String>] [-ShowInPortal] [-Tag <Hashtable>] [-DefaultProfile <PSObject>] [-Break]

[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]

[-WhatIf] [-Confirm] [<CommonParameters>]

Update-AzWvdApplication -InputObject <IDesktopVirtualizationIdentity> [-ApplicationType <RemoteApplicationType>] [-CommandLineArgument <String>] [-CommandLineSetting

<CommandLineSetting>] [-Description <String>] [-FilePath <String>] [-FriendlyName <String>] [-IconIndex <Int32>]
 [-IconPath <String>] [-MsixPackageApplicationId
 <String>] [-MsixPackageFamilyName <String>] [-ShowInPortal] [-Tag <Hashtable>] [-DefaultProfile <PSObject>] [-Break]
 [-HttpPipelineAppend <SendAsyncStep[]>]
 [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
 [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION

Update an application.

PARAMETERS

-GroupName <String>

The name of the application group

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Name <String>

The name of the application within the specified application group

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

The ID of the target subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <IDesktopVirtualizationIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-ApplicationType <RemoteApplicationType>

Resource Type of Application.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-CommandLineArgument <String>

Command Line Arguments for Application.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-CommandLineSetting <CommandLineSetting>

Specifies whether this published application can be launched with command line arguments provided by the client, command line arguments specified at publish time, or no command line arguments at all.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Description <String>

Description of Application.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-FilePath <String>

Specifies a path for the executable file for the application.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-FriendlyName <String>

Friendly name of Application.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-IconIndex <Int32>

Index of the icon.

Required? false

Position? named

Default value 0

Accept pipeline input? false

Accept wildcard characters? false

-IconPath <String>

Path to icon.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-MsixPackageApplicationId <String>

Specifies the package application Id for MSIX applications

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-MsixPackageFamilyName <String>

Specifies the package family name for MSIX applications

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ShowInPortal [<SwitchParameter>]

Specifies whether to show the RemoteApp program in the RD Web Access server.

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Tag <Hashtable>

tags to be updated

Required? false

Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false
Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.DesktopVirtualization.Models.IDesktopVirtualizationIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.DesktopVirtualization.Models.Api20230905.IApplication

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help about_Hash_Tables.

INPUTOBJECT <IDesktopVirtualizationIdentity>: Identity Parameter

[ApplicationGroupName <String>]: The name of the application group

[ApplicationName <String>]: The name of the application within the specified application group

[DesktopName <String>]: The name of the desktop within the specified desktop group

[HostPoolName <String>]: The name of the host pool within the specified resource group

[Id <String>]: Resource identity path

[MsixPackageFullName <String>]: The version specific package full name of the MSIX package within specified hostpool

[PrivateEndpointConnectionName <String>]: The name of the private endpoint connection associated with the Azure resource

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[ScalingPlanName <String>]: The name of the scaling plan.

[ScalingPlanScheduleName <String>]: The name of the ScalingPlanSchedule

[SessionHostName <String>]: The name of the session host within the specified host pool

[SubscriptionId <String>]: The ID of the target subscription.

[UserSessionId <String>]: The name of the user session within the specified session host

[WorkspaceName <String>]: The name of the workspace

----- EXAMPLE 1 -----

```
PS C:\>Update-AzWvdApplication -ResourceGroupName ResourceGroupName `
-GroupName ApplicationGroupName `
-Name ApplicationName `
```

```
-FilePath 'C:\windows\system32\mspaint.exe' `
-FriendlyName 'Friendly name' `
-Description 'Description' `
-IconIndex 0 `
-IconPath 'C:\windows\system32\mspaint.exe' `
-CommandLineSetting 'Allow' `
-ShowInPortal:$true
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.desktopvirtualization/update-azwvdapplication>