



## **Red Hat Enterprise Linux Release 9.2 Manual Pages on 'ASYNC\_callback\_fn.3oss1' command**

**\$ man ASYNC\_callback\_fn.3oss1**

ASYNC\_WAIT\_CTX\_NEW(3oss1)      OpenSSL      ASYNC\_WAIT\_CTX\_NEW(3oss1)

### NAME

ASYNC\_WAIT\_CTX\_new, ASYNC\_WAIT\_CTX\_free, ASYNC\_WAIT\_CTX\_set\_wait\_fd,  
ASYNC\_WAIT\_CTX\_get\_fd, ASYNC\_WAIT\_CTX\_get\_all\_fds,  
ASYNC\_WAIT\_CTX\_get\_changed\_fds, ASYNC\_WAIT\_CTX\_clear\_fd,  
ASYNC\_WAIT\_CTX\_set\_callback, ASYNC\_WAIT\_CTX\_get\_callback,  
ASYNC\_WAIT\_CTX\_set\_status, ASYNC\_WAIT\_CTX\_get\_status,  
ASYNC\_callback\_fn, ASYNC\_STATUS\_UNSUPPORTED, ASYNC\_STATUS\_ERR,  
ASYNC\_STATUS\_OK, ASYNC\_STATUS\_EAGAIN - functions to manage waiting for  
asynchronous jobs to complete

### SYNOPSIS

```
#include <openssl/async.h>

#define ASYNC_STATUS_UNSUPPORTED 0

#define ASYNC_STATUS_ERR      1

#define ASYNC_STATUS_OK      2

#define ASYNC_STATUS_EAGAIN   3

typedef int (*ASYNC_callback_fn)(void *arg);

ASYNC_WAIT_CTX *ASYNC_WAIT_CTX_new(void);

void ASYNC_WAIT_CTX_free(ASYNC_WAIT_CTX *ctx);

int ASYNC_WAIT_CTX_set_wait_fd(ASYNC_WAIT_CTX *ctx, const void *key,
                               OSSL_ASYNC_FD fd,
                               void *custom_data,
                               void (*cleanup)(ASYNC_WAIT_CTX *, const void *,
```

```

        OSSL_ASYNC_FD, void *));
int ASYNC_WAIT_CTX_get_fd(ASYNC_WAIT_CTX *ctx, const void *key,
        OSSL_ASYNC_FD *fd, void **custom_data);
int ASYNC_WAIT_CTX_get_all_fds(ASYNC_WAIT_CTX *ctx, OSSL_ASYNC_FD *fd,
        size_t *numfds);
int ASYNC_WAIT_CTX_get_changed_fds(ASYNC_WAIT_CTX *ctx, OSSL_ASYNC_FD *addfd,
        size_t *numaddfds, OSSL_ASYNC_FD *delfd,
        size_t *numdelfds);
int ASYNC_WAIT_CTX_clear_fd(ASYNC_WAIT_CTX *ctx, const void *key);
int ASYNC_WAIT_CTX_set_callback(ASYNC_WAIT_CTX *ctx,
        ASYNC_callback_fn callback,
        void *callback_arg);
int ASYNC_WAIT_CTX_get_callback(ASYNC_WAIT_CTX *ctx,
        ASYNC_callback_fn *callback,
        void **callback_arg);
int ASYNC_WAIT_CTX_set_status(ASYNC_WAIT_CTX *ctx, int status);
int ASYNC_WAIT_CTX_get_status(ASYNC_WAIT_CTX *ctx);

```

## DESCRIPTION

For an overview of how asynchronous operations are implemented in OpenSSL see `ASYNC_start_job(3)`. An `ASYNC_WAIT_CTX` object represents an asynchronous "session", i.e. a related set of crypto operations. For example in SSL terms this would have a one-to-one correspondence with an SSL connection.

Application code must create an `ASYNC_WAIT_CTX` using the `ASYNC_WAIT_CTX_new()` function prior to calling `ASYNC_start_job()` (see `ASYNC_start_job(3)`). When the job is started it is associated with the `ASYNC_WAIT_CTX` for the duration of that job. An `ASYNC_WAIT_CTX` should only be used for one `ASYNC_JOB` at any one time, but can be reused after an `ASYNC_JOB` has finished for a subsequent `ASYNC_JOB`. When the session is complete (e.g. the SSL connection is closed), application code cleans up with `ASYNC_WAIT_CTX_free()`.

`ASYNC_WAIT_CTX`s can have "wait" file descriptors associated with them.

Calling `ASYNC_WAIT_CTX_get_all_fds()` and passing in a pointer to an

ASYNC\_WAIT\_CTX in the ctx parameter will return the wait file descriptors associated with that job in \*fd. The number of file descriptors returned will be stored in \*numfds. It is the caller's responsibility to ensure that sufficient memory has been allocated in \*fd to receive all the file descriptors. Calling ASYNC\_WAIT\_CTX\_get\_all\_fds() with a NULL fd value will return no file descriptors but will still populate \*numfds. Therefore, application code is typically expected to call this function twice: once to get the number of fds, and then again when sufficient memory has been allocated. If only one asynchronous engine is being used then normally this call will only ever return one fd. If multiple asynchronous engines are being used then more could be returned.

The function ASYNC\_WAIT\_CTX\_get\_changed\_fds() can be used to detect if any fds have changed since the last call time ASYNC\_start\_job() returned ASYNC\_PAUSE (or since the ASYNC\_WAIT\_CTX was created if no ASYNC\_PAUSE result has been received). The numaddfds and numdelfds parameters will be populated with the number of fds added or deleted respectively. \*addfd and \*delfd will be populated with the list of added and deleted fds respectively. Similarly to ASYNC\_WAIT\_CTX\_get\_all\_fds() either of these can be NULL, but if they are not NULL then the caller is responsible for ensuring sufficient memory is allocated.

Implementors of async aware code (e.g. engines) are encouraged to return a stable fd for the lifetime of the ASYNC\_WAIT\_CTX in order to reduce the "churn" of regularly changing fds - although no guarantees of this are provided to applications.

Applications can wait for the file descriptor to be ready for "read" using a system function call such as select or poll (being ready for "read" indicates that the job should be resumed). If no file descriptor is made available then an application will have to periodically "poll" the job by attempting to restart it to see if it is ready to continue.

Async aware code (e.g. engines) can get the current ASYNC\_WAIT\_CTX from the job via ASYNC\_get\_wait\_ctx(3) and provide a file descriptor to use

for waiting on by calling `ASYNC_WAIT_CTX_set_wait_fd()`. Typically this would be done by an engine immediately prior to calling `ASYNC_pause_job()` and not by end user code. An existing association with a file descriptor can be obtained using `ASYNC_WAIT_CTX_get_fd()` and cleared using `ASYNC_WAIT_CTX_clear_fd()`. Both of these functions requires a key value which is unique to the async aware code. This could be any unique value but a good candidate might be the `ENGINE *` for the engine. The `custom_data` parameter can be any value, and will be returned in a subsequent call to `ASYNC_WAIT_CTX_get_fd()`. The `ASYNC_WAIT_CTX_set_wait_fd()` function also expects a pointer to a "cleanup" routine. This can be `NULL` but if provided will automatically get called when the `ASYNC_WAIT_CTX` is freed, and gives the engine the opportunity to close the fd or any other resources. Note: The "cleanup" routine does not get called if the fd is cleared directly via a call to `ASYNC_WAIT_CTX_clear_fd()`.

An example of typical usage might be an async capable engine. User code would initiate cryptographic operations. The engine would initiate those operations asynchronously and then call `ASYNC_WAIT_CTX_set_wait_fd()` followed by `ASYNC_pause_job()` to return control to the user code. The user code can then perform other tasks or wait for the job to be ready by calling "select" or other similar function on the wait file descriptor. The engine can signal to the user code that the job should be resumed by making the wait file descriptor "readable". Once resumed the engine should clear the wake signal on the wait file descriptor.

As well as a file descriptor, user code may also be notified via a callback. The callback and data pointers are stored within the `ASYNC_WAIT_CTX` along with an additional status field that can be used for the notification of retries from an engine. This additional method can be used when the user thinks that a file descriptor is too costly in terms of CPU cycles or in some context where a file descriptor is not appropriate.

`ASYNC_WAIT_CTX_set_callback()` sets the callback and the callback

argument. The callback will be called to notify user code when an engine completes a cryptography operation. It is a requirement that the callback function is small and nonblocking as it will be run in the context of a polling mechanism or an interrupt.

`ASYNC_WAIT_CTX_get_callback()` returns the callback set in the `ASYNC_WAIT_CTX` structure.

`ASYNC_WAIT_CTX_set_status()` allows an engine to set the current engine status. The possible status values are the following:

#### `ASYNC_STATUS_UNSUPPORTED`

The engine does not support the callback mechanism. This is the default value. The engine must call `ASYNC_WAIT_CTX_set_status()` to set the status to some value other than `ASYNC_STATUS_UNSUPPORTED` if it intends to enable the callback mechanism.

#### `ASYNC_STATUS_ERR`

The engine has a fatal problem with this request. The user code should clean up this session.

#### `ASYNC_STATUS_OK`

The request has been successfully submitted.

#### `ASYNC_STATUS_EAGAIN`

The engine has some problem which will be recovered soon, such as a buffer is full, so user code should resume the job.

`ASYNC_WAIT_CTX_get_status()` allows user code to obtain the current status value. If the status is any value other than `ASYNC_STATUS_OK` then the user code should not expect to receive a callback from the engine even if one has been set.

An example of the usage of the callback method might be the following. User code would initiate cryptographic operations, and the engine code would dispatch this operation to hardware, and if the dispatch is successful, then the engine code would call `ASYNC_pause_job()` to return control to the user code. After that, user code can perform other tasks. When the hardware completes the operation, normally it is detected by a polling function or an interrupt, as the user code set a callback by calling `ASYNC_WAIT_CTX_set_callback()` previously, then the

registered callback will be called.

## RETURN VALUES

ASYNC\_WAIT\_CTX\_new() returns a pointer to the newly allocated

ASYNC\_WAIT\_CTX or NULL on error.

ASYNC\_WAIT\_CTX\_set\_wait\_fd, ASYNC\_WAIT\_CTX\_get\_fd,

ASYNC\_WAIT\_CTX\_get\_all\_fds, ASYNC\_WAIT\_CTX\_get\_changed\_fds,

ASYNC\_WAIT\_CTX\_clear\_fd, ASYNC\_WAIT\_CTX\_set\_callback,

ASYNC\_WAIT\_CTX\_get\_callback and ASYNC\_WAIT\_CTX\_set\_status all return 1

on success or 0 on error. ASYNC\_WAIT\_CTX\_get\_status() returns the engine status.

## NOTES

On Windows platforms the `<openssl/async.h>` header is dependent on some of the types customarily made available by including `<windows.h>`. The application developer is likely to require control over when the latter is included, commonly as one of the first included headers. Therefore, it is defined as an application developer's responsibility to include `<windows.h>` prior to `<openssl/async.h>`.

## SEE ALSO

crypto(7), ASYNC\_start\_job(3)

## HISTORY

ASYNC\_WAIT\_CTX\_new(), ASYNC\_WAIT\_CTX\_free(),

ASYNC\_WAIT\_CTX\_set\_wait\_fd(), ASYNC\_WAIT\_CTX\_get\_fd(),

ASYNC\_WAIT\_CTX\_get\_all\_fds(), ASYNC\_WAIT\_CTX\_get\_changed\_fds() and

ASYNC\_WAIT\_CTX\_clear\_fd() were added in OpenSSL 1.1.0.

ASYNC\_WAIT\_CTX\_set\_callback(), ASYNC\_WAIT\_CTX\_get\_callback(),

ASYNC\_WAIT\_CTX\_set\_status(), and ASYNC\_WAIT\_CTX\_get\_status() were added

in OpenSSL 3.0.

## COPYRIGHT

Copyright 2016-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use

this file except in compliance with the License. You can obtain a copy

in the file LICENSE in the source distribution or at

<https://www.openssl.org/source/license.html>.

