



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'CMS_AuthEnvelopedData_create_ex.3ossl' command

```
$ man CMS_AuthEnvelopedData_create_ex.3ossl
```

```
CMS_ENVELOPEDDATA_CREATE(3ossl)  OpenSSL  CMS_ENVELOPEDDATA_CREATE(3ossl)
```

NAME

CMS_EnvelopedData_create_ex, CMS_EnvelopedData_create,
CMS_AuthEnvelopedData_create, CMS_AuthEnvelopedData_create_ex - Create
CMS envelope

SYNOPSIS

```
#include <openssl/cms.h>
```

```
CMS_ContentInfo *
```

```
CMS_EnvelopedData_create_ex(const EVP_CIPHER *cipher, OSSL_LIB_CTX *libctx,  
                             const char *propq);
```

```
CMS_ContentInfo *CMS_EnvelopedData_create(const EVP_CIPHER *cipher);
```

```
CMS_ContentInfo *
```

```
CMS_AuthEnvelopedData_create_ex(const EVP_CIPHER *cipher, OSSL_LIB_CTX *libctx,  
                                 const char *propq);
```

```
CMS_ContentInfo *CMS_AuthEnvelopedData_create(const EVP_CIPHER *cipher);
```

DESCRIPTION

CMS_EnvelopedData_create_ex() creates a CMS_ContentInfo structure with
a type NID_pkcs7_enveloped. cipher is the symmetric cipher to use. The

library context `libctx` and the property query `propq` are used when retrieving algorithms from providers.

`CMS_AuthEnvelopedData_create_ex()` creates a `CMS_ContentInfo` structure with a type `NID_id_smime_ct_authEnvelopedData`. `cipher` is the symmetric AEAD cipher to use. Currently only AES variants with GCM mode are supported. The library context `libctx` and the property query `propq` are used when retrieving algorithms from providers.

The algorithm passed in the `cipher` parameter must support ASN1 encoding of its parameters.

The recipients can be added later using `CMS_add1_recipient_cert(3)` or `CMS_add0_recipient_key(3)`.

The `CMS_ContentInfo` structure needs to be finalized using `CMS_final(3)` and then freed using `CMS_ContentInfo_free(3)`.

`CMS_EnvelopedData_create()` and `CMS_AuthEnvelopedData_create` are similar to `CMS_EnvelopedData_create_ex()` and `CMS_AuthEnvelopedData_create_ex()` but use default values of `NULL` for the library context `libctx` and the property query `propq`.

NOTES

Although `CMS_EnvelopedData_create()` and `CMS_AuthEnvelopedData_create()` allocate a new `CMS_ContentInfo` structure, they are not usually used in applications. The wrappers `CMS_encrypt(3)` and `CMS_decrypt(3)` are often used instead.

RETURN VALUES

If the allocation fails, `CMS_EnvelopedData_create()` and `CMS_AuthEnvelopedData_create()` return `NULL` and set an error code that can be obtained by `ERR_get_error(3)`. Otherwise they return a pointer to

the newly allocated structure.

SEE ALSO

`ERR_get_error(3)`, `CMS_encrypt(3)`, `CMS_decrypt(3)`, `CMS_final(3)`

HISTORY

The `CMS_EnvelopedData_create_ex()` method was added in OpenSSL 3.0.

COPYRIGHT

Copyright 2020-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file `LICENSE` in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7 2023-07-13 `CMS_ENVELOPEDDATA_CREATE(3openssl)`