



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## ***Red Hat Enterprise Linux Release 9.2 Manual Pages on 'CMS\_add1\_signer.3oss1' command***

***\$ man CMS\_add1\_signer.3oss1***

CMS\_ADD1\_SIGNER(3oss1)      OpenSSL      CMS\_ADD1\_SIGNER(3oss1)

### NAME

CMS\_add1\_signer, CMS\_SignerInfo\_sign - add a signer to a CMS\_ContentInfo signed data structure

### SYNOPSIS

```
#include <openssl/cms.h>
```

```
CMS_SignerInfo *CMS_add1_signer(CMS_ContentInfo *cms, X509 *signcert,  
                                EVP_PKEY *pkey, const EVP_MD *md,  
                                unsigned int flags);
```

```
int CMS_SignerInfo_sign(CMS_SignerInfo *si);
```

### DESCRIPTION

CMS\_add1\_signer() adds a signer with certificate signcert and private key pkey using message digest md to CMS\_ContentInfo SignedData structure cms.

The CMS\_ContentInfo structure should be obtained from an initial call to CMS\_sign() with the flag CMS\_PARTIAL set or in the case or re-signing a valid CMS\_ContentInfo SignedData structure.

If the md parameter is NULL then the default digest for the public key algorithm will be used.

Unless the CMS\_REUSE\_DIGEST flag is set the returned CMS\_ContentInfo structure is not complete and must be finalized either by streaming (if applicable) or a call to CMS\_final().

The CMS\_SignerInfo\_sign() function will explicitly sign a CMS\_SignerInfo structure, its main use is when CMS\_REUSE\_DIGEST and CMS\_PARTIAL flags are both set.

## NOTES

The main purpose of CMS\_add1\_signer() is to provide finer control over a CMS signed data structure where the simpler CMS\_sign() function defaults are not appropriate. For example if multiple signers or non default digest algorithms are needed. New attributes can also be added using the returned CMS\_SignerInfo structure and the CMS attribute utility functions or the CMS signed receipt request functions.

Any of the following flags (ored together) can be passed in the flags parameter.

If CMS\_REUSE\_DIGEST is set then an attempt is made to copy the content digest value from the CMS\_ContentInfo structure: to add a signer to an existing structure. An error occurs if a matching digest value cannot be found to copy. The returned CMS\_ContentInfo structure will be valid and finalized when this flag is set.

If CMS\_PARTIAL is set in addition to CMS\_REUSE\_DIGEST then the CMS\_SignerInfo structure will not be finalized so additional attributes can be added. In this case an explicit call to CMS\_SignerInfo\_sign() is needed to finalize it.

If CMS\_NOCERTS is set the signer's certificate will not be included in the CMS\_ContentInfo structure, the signer's certificate must still be supplied in the signcert parameter though. This can reduce the size of the signature if the signers certificate can be obtained by other means: for example a previously signed message.

The SignedData structure includes several CMS signedAttributes including the signing time, the CMS content type and the supported list of ciphers in an SMIMECapabilities attribute. If CMS\_NOATTR is set then no signedAttributes will be used. If CMS\_NOSMIMECAP is set then just the SMIMECapabilities are omitted.

OpenSSL will by default identify signing certificates using issuer name and serial number. If CMS\_USE\_KEYID is set it will use the subject key identifier value instead. An error occurs if the signing certificate does not have a subject key identifier extension.

If present the SMIMECapabilities attribute indicates support for the following algorithms in preference order: 256 bit AES, Gost R3411-94, Gost 28147-89, 192 bit AES, 128 bit AES, triple DES, 128 bit RC2, 64 bit RC2, DES and 40 bit RC2. If any of these algorithms is not available then it will not be included: for example the GOST algorithms will not be included if the GOST ENGINE is not loaded.

CMS\_add1\_signer() returns an internal pointer to the CMS\_SignerInfo structure just added, this can be used to set additional attributes before it is finalized.

## RETURN VALUES

CMS\_add1\_signer() returns an internal pointer to the CMS\_SignerInfo structure just added or NULL if an error occurs.

## SEE ALSO

ERR\_get\_error(3), CMS\_sign(3), CMS\_final(3),

## COPYRIGHT

Copyright 2014-2016 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7                    2023-07-13           CMS\_ADD1\_SIGNER(3ossl)