



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'CONF_modules_finish.3ossl' command

\$ man CONF_modules_finish.3ossl

CONF_MODULES_FREE(3ossl) OpenSSL CONF_MODULES_FREE(3ossl)

NAME

CONF_modules_free, CONF_modules_finish, CONF_modules_unload - OpenSSL configuration cleanup functions

SYNOPSIS

```
#include <openssl/conf.h>
```

```
void CONF_modules_finish(void);
```

```
void CONF_modules_unload(int all);
```

The following functions have been deprecated since OpenSSL 1.1.0, and can be hidden entirely by defining OPENSSL_API_COMPAT with a suitable version value, see openssl_user_macros(7):

```
void CONF_modules_free(void);
```

DESCRIPTION

CONF_modules_free() closes down and frees up all memory allocated by all configuration modules. Normally, in versions of OpenSSL prior to 1.1.0, applications called CONF_modules_free() at exit to tidy up any configuration performed.

CONF_modules_finish() calls each configuration modules finish handler to free up any configuration that module may have performed.

CONF_modules_unload() finishes and unloads configuration modules. If all is set to 0 only modules loaded from DSOs will be unloads. If all is 1 all modules, including built-in modules will be unloaded.

RETURN VALUES

None of the functions return a value.

SEE ALSO

config(5), OPENSSL_config(3), CONF_modules_load_file_ex(3)

HISTORY

CONF_modules_free() was deprecated in OpenSSL 1.1.0; do not use it.

For more information see OPENSSL_init_crypto(3).

COPYRIGHT

Copyright 2004-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7 2023-07-13 CONF_MODULES_FREE(3ossl)