



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'DH_get_nid.3oss1' command

\$ man DH_get_nid.3oss1

DH_NEW_BY_NID(3oss1) OpenSSL DH_NEW_BY_NID(3oss1)

NAME

DH_new_by_nid, DH_get_nid - create or get DH named parameters

SYNOPSIS

```
#include <openssl/dh.h>
```

The following functions have been deprecated since OpenSSL 3.0, and can be hidden entirely by defining OPENSSL_API_COMPAT with a suitable version value, see openssl_user_macros(7):

```
DH *DH_new_by_nid(int nid);
```

```
int DH_get_nid(const DH *dh);
```

DESCRIPTION

DH_new_by_nid() creates and returns a DH structure containing named parameters nid. Currently nid must be NID_ffdhe2048, NID_ffdhe3072, NID_ffdhe4096, NID_ffdhe6144, NID_ffdhe8192, NID_modp_1536, NID_modp_2048, NID_modp_3072, NID_modp_4096, NID_modp_6144 or NID_modp_8192.

DH_get_nid() determines if the parameters contained in dh match any named safe prime group. It returns the NID corresponding to the matching parameters or NID_undef if there is no match. This function is deprecated.

RETURN VALUES

DH_new_by_nid() returns a set of DH parameters or NULL if an error occurred.

DH_get_nid() returns the NID of the matching set of parameters for p and g and optionally q, otherwise it returns NID_undef if there is no match.

HISTORY

All of these functions were deprecated in OpenSSL 3.0.

COPYRIGHT

Copyright 2017-2022 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7 2023-07-13 DH_NEW_BY_NID(3ossl)