



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'ERR_load_crypto_strings.3oss1' command

```
$ man ERR_load_crypto_strings.3oss1
```

```
ERR_LOAD_CRYPTOSTRINGS(3oss1)  OpenSSL  ERR_LOAD_CRYPTOSTRINGS(3oss1)
```

NAME

ERR_load_crypto_strings, SSL_load_error_strings, ERR_free_strings -
load and free error strings

SYNOPSIS

The following functions have been deprecated since OpenSSL 1.1.0, and can be hidden entirely by defining OPENSSL_API_COMPAT with a suitable version value, see openssl_user_macros(7):

```
#include <openssl/err.h>
```

```
void ERR_load_crypto_strings(void);
```

```
void ERR_free_strings(void);
```

```
#include <openssl/ssl.h>
```

```
void SSL_load_error_strings(void);
```

DESCRIPTION

ERR_load_crypto_strings() registers the error strings for all libcrypto functions. SSL_load_error_strings() does the same, but also registers

the libssl error strings.

In versions prior to OpenSSL 1.1.0, `ERR_free_strings()` releases any resources created by the above functions.

RETURN VALUES

`ERR_load_crypto_strings()`, `SSL_load_error_strings()` and `ERR_free_strings()` return no values.

SEE ALSO

`ERR_error_string(3)`

HISTORY

The `ERR_load_crypto_strings()`, `SSL_load_error_strings()`, and `ERR_free_strings()` functions were deprecated in OpenSSL 1.1.0 by `OPENSSL_init_crypto()` and `OPENSSL_init_ssl()` and should not be used.

COPYRIGHT

Copyright 2000-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file `LICENSE` in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7 2023-07-13 ERR_LOAD_CRYPT0_STRINGS(30ssl)