



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'EVP_KDF-PBKDF2.7oss!' command

\$ man EVP_KDF-PBKDF2.7oss!

EVP_KDF-PBKDF2(7oss!) OpenSSL EVP_KDF-PBKDF2(7oss!)

NAME

EVP_KDF-PBKDF2 - The PBKDF2 EVP_KDF implementation

DESCRIPTION

Support for computing the PBKDF2 password-based KDF through the EVP_KDF API.

The EVP_KDF-PBKDF2 algorithm implements the PBKDF2 password-based key derivation function, as described in SP800-132; it derives a key from a password using a salt and iteration count.

Identity

"PBKDF2" is the name for this implementation; it can be used with the EVP_KDF_fetch() function.

Supported parameters

The supported parameters are:

"pass" (OSSL_KDF_PARAM_PASSWORD) <octet string>

"salt" (OSSL_KDF_PARAM_SALT) <octet string>

"iter" (OSSL_KDF_PARAM_ITER) <unsigned integer>

This parameter has a default value of 2048.

"properties" (OSSL_KDF_PARAM_PROPERTIES) <UTF8 string>

"digest" (OSSL_KDF_PARAM_DIGEST) <UTF8 string>

These parameters work as described in "PARAMETERS" in EVP_KDF(3).

"pkcs5" (OSSL_KDF_PARAM_PKCS5) <integer>

This parameter can be used to enable or disable SP800-132 compliance checks. Setting the mode to 0 enables the compliance checks.

The checks performed are:

- the iteration count is at least 1000.
- the salt length is at least 128 bits.
- the derived key length is at least 112 bits.

The default provider uses a default mode of 1 for backwards compatibility, and the FIPS provider uses a default mode of 0.

The value string is expected to be a decimal number 0 or 1.

NOTES

A typical application of this algorithm is to derive keying material for an encryption algorithm from a password in the "pass", a salt in "salt", and an iteration count.

Increasing the "iter" parameter slows down the algorithm which makes it harder for an attacker to perform a brute force attack using a large number of candidate passwords.

No assumption is made regarding the given password; it is simply treated as a byte sequence.

CONFORMING TO

SP800-132

SEE ALSO

EVP_KDF(3), EVP_KDF_CTX_new(3), EVP_KDF_CTX_free(3),
EVP_KDF_CTX_set_params(3), EVP_KDF_derive(3), "PARAMETERS" in
EVP_KDF(3)

HISTORY

This functionality was added to OpenSSL 3.0.

COPYRIGHT

Copyright 2018-2022 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use
this file except in compliance with the License. You can obtain a copy
in the file LICENSE in the source distribution or at
<<https://www.openssl.org/source/license.html>>.

3.0.7 2023-07-13 EVP_KDF-PBKDF2(7ossl)