



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'EVP_MD-SHA1.7oss1' command

\$ man EVP_MD-SHA1.7oss1

EVP_MD-SHA1(7oss1) OpenSSL EVP_MD-SHA1(7oss1)

NAME

EVP_MD-SHA1 - The SHA1 EVP_MD implementation

DESCRIPTION

Support for computing SHA1 digests through the EVP_MD API.

Identities

This implementation is available with the FIPS provider as well as the default provider, and is identified with the names "SHA1" and "SHA-1".

Gettable Parameters

This implementation supports the common gettable parameters described in EVP_MD-common(7).

Settable Context Parameters

This implementation supports the following OSSL_PARAM(3) entries, settable for an EVP_MD_CTX with EVP_MD_CTX_set_params(3):

"ssl3-ms" (OSSL_DIGEST_PARAM_SSL3_MS) <octet string>

This parameter is set by libssl in order to calculate a signature hash for an SSLv3 CertificateVerify message as per RFC6101. It is

only set after all handshake messages have already been digested via `OP_digest_update()` calls. The parameter provides the master secret value to be added to the digest. The digest implementation should calculate the complete digest as per RFC6101 section 5.6.8. The next call after setting this parameter should be `OP_digest_final()`.

SEE ALSO

`EVP_MD_CTX_set_params(3)`, `provider-digest(7)`, `OSSL_PROVIDER-FIPS(7)`, `OSSL_PROVIDER-default(7)`

COPYRIGHT

Copyright 2020 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file `LICENSE` in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7

2023-07-13

EVP_MD-SHA1(7ossl)