



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## **Red Hat Enterprise Linux Release 9.2 Manual Pages on 'EVP\_PKCS82PKEY.3ossl' command**

**\$ man EVP\_PKCS82PKEY.3ossl**

EVP\_PKEY2PKCS8(3ossl)      OpenSSL      EVP\_PKEY2PKCS8(3ossl)

### NAME

EVP\_PKEY2PKCS8, EVP\_PKCS82PKEY\_ex, EVP\_PKCS82PKEY - Convert a private key to/from PKCS8

### SYNOPSIS

```
#include <openssl/x509.h>
```

```
PKCS8_PRIV_KEY_INFO *EVP_PKEY2PKCS8(const EVP_PKEY *pkey);
```

```
EVP_PKEY *EVP_PKCS82PKEY(const PKCS8_PRIV_KEY_INFO *p8);
```

```
EVP_PKEY *EVP_PKCS82PKEY_ex(const PKCS8_PRIV_KEY_INFO *p8, OSSL_LIB_CTX *libctx,  
const char *propq);
```

### DESCRIPTION

EVP\_PKEY2PKCS8() converts a private key pkey into a returned PKCS8 object.

EVP\_PKCS82PKEY\_ex() converts a PKCS8 object p8 into a returned private key. It uses libctx and propq when fetching algorithms.

EVP\_PKCS82PKEY() is similar to EVP\_PKCS82PKEY\_ex() but uses default values of NULL for the libctx and propq.

## RETURN VALUES

EVP\_PKEY2PKCS8() returns a PKCS8 object on success. EVP\_PKCS82PKEY() and EVP\_PKCS82PKEY\_ex() return a private key on success.

All functions return NULL if the operation fails.

## SEE ALSO

PKCS8\_pkey\_add1\_attr(3),

## COPYRIGHT

Copyright 2020 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.

3.0.7                      2023-07-13              EVP\_PKEY2PKCS8(3ossl)