



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'EVP_PKEY_get1_EC_KEY.3oss1' command

`$ man EVP_PKEY_get1_EC_KEY.3oss1`

EVP_PKEY_SET1_RSA(3oss1) OpenSSL EVP_PKEY_SET1_RSA(3oss1)

NAME

EVP_PKEY_set1_RSA, EVP_PKEY_set1_DSA, EVP_PKEY_set1_DH,
EVP_PKEY_set1_EC_KEY, EVP_PKEY_get1_RSA, EVP_PKEY_get1_DSA,
EVP_PKEY_get1_DH, EVP_PKEY_get1_EC_KEY, EVP_PKEY_get0_RSA,
EVP_PKEY_get0_DSA, EVP_PKEY_get0_DH, EVP_PKEY_get0_EC_KEY,
EVP_PKEY_assign_RSA, EVP_PKEY_assign_DSA, EVP_PKEY_assign_DH,
EVP_PKEY_assign_EC_KEY, EVP_PKEY_assign_POLY1305,
EVP_PKEY_assign_SIPHASH, EVP_PKEY_get0_hmac, EVP_PKEY_get0_poly1305,
EVP_PKEY_get0_siphhash, EVP_PKEY_get0, EVP_PKEY_type, EVP_PKEY_get_id,
EVP_PKEY_get_base_id, EVP_PKEY_set1_engine, EVP_PKEY_get0_engine,
EVP_PKEY_id, EVP_PKEY_base_id - EVP_PKEY assignment functions

SYNOPSIS

```
#include <openssl/evp.h>

int EVP_PKEY_get_id(const EVP_PKEY *pkey);

int EVP_PKEY_get_base_id(const EVP_PKEY *pkey);

int EVP_PKEY_type(int type);

#define EVP_PKEY_id EVP_PKEY_get_id

#define EVP_PKEY_base_id EVP_PKEY_get_base_id
```

The following functions have been deprecated since OpenSSL 3.0, and can be hidden entirely by defining OPENSSL_API_COMPAT with a suitable version value, see openssl_user_macros(7):

```
int EVP_PKEY_set1_RSA(EVP_PKEY *pkey, RSA *key);
```

```

int EVP_PKEY_set1_DSA(EVP_PKEY *pkey, DSA *key);
int EVP_PKEY_set1_DH(EVP_PKEY *pkey, DH *key);
int EVP_PKEY_set1_EC_KEY(EVP_PKEY *pkey, EC_KEY *key);
RSA *EVP_PKEY_get1_RSA(EVP_PKEY *pkey);
DSA *EVP_PKEY_get1_DSA(EVP_PKEY *pkey);
DH *EVP_PKEY_get1_DH(EVP_PKEY *pkey);
EC_KEY *EVP_PKEY_get1_EC_KEY(EVP_PKEY *pkey);
const unsigned char *EVP_PKEY_get0_hmac(const EVP_PKEY *pkey, size_t *len);
const unsigned char *EVP_PKEY_get0_poly1305(const EVP_PKEY *pkey, size_t *len);
const unsigned char *EVP_PKEY_get0_siphhash(const EVP_PKEY *pkey, size_t *len);
const RSA *EVP_PKEY_get0_RSA(const EVP_PKEY *pkey);
const DSA *EVP_PKEY_get0_DSA(const EVP_PKEY *pkey);
const DH *EVP_PKEY_get0_DH(const EVP_PKEY *pkey);
const EC_KEY *EVP_PKEY_get0_EC_KEY(const EVP_PKEY *pkey);
void *EVP_PKEY_get0(const EVP_PKEY *pkey);
int EVP_PKEY_assign_RSA(EVP_PKEY *pkey, RSA *key);
int EVP_PKEY_assign_DSA(EVP_PKEY *pkey, DSA *key);
int EVP_PKEY_assign_DH(EVP_PKEY *pkey, DH *key);
int EVP_PKEY_assign_EC_KEY(EVP_PKEY *pkey, EC_KEY *key);
int EVP_PKEY_assign_POLY1305(EVP_PKEY *pkey, ASN1_OCTET_STRING *key);
int EVP_PKEY_assign_SIPHASH(EVP_PKEY *pkey, ASN1_OCTET_STRING *key);
ENGINE *EVP_PKEY_get0_engine(const EVP_PKEY *pkey);
int EVP_PKEY_set1_engine(EVP_PKEY *pkey, ENGINE *engine);

```

DESCRIPTION

`EVP_PKEY_get_base_id()` returns the type of pkey. For example an RSA key will return `EVP_PKEY_RSA`.

`EVP_PKEY_get_id()` returns the actual OID associated with pkey.

Historically keys using the same algorithm could use different OIDs.

For example an RSA key could use the OIDs corresponding to the NIDs

`NID_rsaEncryption` (equivalent to `EVP_PKEY_RSA`) or `NID_rsa` (equivalent

to `EVP_PKEY_RSA2`). The use of alternative non-standard OIDs is now rare

so `EVP_PKEY_RSA2` et al are not often seen in practice.

`EVP_PKEY_type()` returns the underlying type of the NID type. For

example `EVP_PKEY_type(EVP_PKEY_RSA2)` will return `EVP_PKEY_RSA`.

`EVP_PKEY_set1_RSA()`, `EVP_PKEY_set1_DSA()`, `EVP_PKEY_set1_DH()` and

`EVP_PKEY_set1_EC_KEY()` set the key referenced by `pkey` to `key`. These

functions are deprecated. Applications should instead use

`EVP_PKEY_fromdata(3)`.

`EVP_PKEY_assign_RSA()`, `EVP_PKEY_assign_DSA()`, `EVP_PKEY_assign_DH()`,

`EVP_PKEY_assign_EC_KEY()`, `EVP_PKEY_assign_POLY1305()` and

`EVP_PKEY_assign_SIPHASH()` set the referenced key to `key` however these

use the supplied key internally and so `key` will be freed when the

parent `pkey` is freed. These macros are deprecated. Applications should

instead read an `EVP_PKEY` directly using the `OSSL_DECODER` APIs (see

`OSSL_DECODER_CTX_new_for_pkey(3)`), or construct an `EVP_PKEY` from data

using `EVP_PKEY_fromdata(3)`.

`EVP_PKEY_get1_RSA()`, `EVP_PKEY_get1_DSA()`, `EVP_PKEY_get1_DH()` and

`EVP_PKEY_get1_EC_KEY()` return the referenced key in `pkey` or `NULL` if the

key is not of the correct type. The returned key must be freed after

use. These functions are deprecated. Applications should instead use

the `EVP_PKEY` directly where possible. If access to the low level key

parameters is required then applications should use

`EVP_PKEY_get_params(3)` and other similar functions. To write an

`EVP_PKEY` out use the `OSSL_ENCODER` APIs (see

`OSSL_ENCODER_CTX_new_for_pkey(3)`).

`EVP_PKEY_get0_hmac()`, `EVP_PKEY_get0_poly1305()`,

`EVP_PKEY_get0_siphash()`, `EVP_PKEY_get0_RSA()`, `EVP_PKEY_get0_DSA()`,

`EVP_PKEY_get0_DH()` and `EVP_PKEY_get0_EC_KEY()` return the referenced key

in `pkey` or `NULL` if the key is not of the correct type. The reference

count of the returned key is not incremented and so the key must not be

freed after use. These functions are deprecated. Applications should

instead use the `EVP_PKEY` directly where possible. If access to the low

level key parameters is required then applications should use

`EVP_PKEY_get_params(3)` and other similar functions. To write an

`EVP_PKEY` out use the `OSSL_ENCODER` APIs (see

`OSSL_ENCODER_CTX_new_for_pkey(3)`). `EVP_PKEY_get0()` returns a pointer to

the legacy key or NULL if the key is not legacy.

Note that if an `EVP_PKEY` was not constructed using one of the deprecated functions such as `EVP_PKEY_set1_RSA()`, `EVP_PKEY_set1_DSA()`, `EVP_PKEY_set1_DH()` or `EVP_PKEY_set1_EC_KEY()`, or via the similarly named `EVP_PKEY_assign` macros described above then the internal key will be managed by a provider (see `provider(7)`). In that case the key returned by `EVP_PKEY_get1_RSA()`, `EVP_PKEY_get1_DSA()`, `EVP_PKEY_get1_DH()`, `EVP_PKEY_get1_EC_KEY()`, `EVP_PKEY_get0_hmac()`, `EVP_PKEY_get0_poly1305()`, `EVP_PKEY_get0_siphhash()`, `EVP_PKEY_get0_RSA()`, `EVP_PKEY_get0_DSA()`, `EVP_PKEY_get0_DH()` or `EVP_PKEY_get0_EC_KEY()` will be a cached copy of the provider's key. Subsequent updates to the provider's key will not be reflected back in the cached copy, and updates made by an application to the returned key will not be reflected back in the provider's key. Subsequent calls to `EVP_PKEY_get1_RSA()`, `EVP_PKEY_get1_DSA()`, `EVP_PKEY_get1_DH()` and `EVP_PKEY_get1_EC_KEY()` will always return the cached copy returned by the first call.

`EVP_PKEY_get0_engine()` returns a reference to the ENGINE handling pkey.

This function is deprecated. Applications should use providers instead of engines (see `provider(7)` for details).

`EVP_PKEY_set1_engine()` sets the ENGINE handling pkey to engine. It must be called after the key algorithm and components are set up. If engine does not include an `EVP_PKEY_METHOD` for pkey an error occurs. This function is deprecated. Applications should use providers instead of engines (see `provider(7)` for details).

WARNINGS

The following functions are only reliable with `EVP_PKEY`s that have been assigned an internal key with `EVP_PKEY_assign_*`:

`EVP_PKEY_get_id()`, `EVP_PKEY_get_base_id()`, `EVP_PKEY_type()`

For `EVP_PKEY` key type checking purposes, `EVP_PKEY_is_a(3)` is more generic.

The keys returned from the functions `EVP_PKEY_get0_RSA()`, `EVP_PKEY_get0_DSA()`, `EVP_PKEY_get0_DH()` and `EVP_PKEY_get0_EC_KEY()` were

changed to have a "const" return type in OpenSSL 3.0. As described above the keys returned may be cached copies of the key held in a provider. Due to this, and unlike in earlier versions of OpenSSL, they should be considered read-only copies of the key. Updates to these keys will not be reflected back in the provider side key. The `EVP_PKEY_get1_RSA()`, `EVP_PKEY_get1_DSA()`, `EVP_PKEY_get1_DH()` and `EVP_PKEY_get1_EC_KEY()` functions were not changed to have a "const" return type in order that applications can "free" the return value. However applications should still consider them as read-only copies.

NOTES

In accordance with the OpenSSL naming convention the key obtained from or assigned to the pkey using the 1 functions must be freed as well as pkey.

`EVP_PKEY_assign_RSA()`, `EVP_PKEY_assign_DSA()`, `EVP_PKEY_assign_DH()`, `EVP_PKEY_assign_EC_KEY()`, `EVP_PKEY_assign_POLY1305()` and `EVP_PKEY_assign_SIPHASH()` are implemented as macros.

`EVP_PKEY_assign_EC_KEY()` looks at the curve name id to determine if the passed `EC_KEY` is an SM2(7) key, and will set the `EVP_PKEY` type to `EVP_PKEY_SM2` in that case, instead of `EVP_PKEY_EC`.

Most applications wishing to know a key type will simply call `EVP_PKEY_get_base_id()` and will not care about the actual type: which will be identical in almost all cases.

Previous versions of this document suggested using `EVP_PKEY_type(pkey->type)` to determine the type of a key. Since `EVP_PKEY` is now opaque this is no longer possible: the equivalent is `EVP_PKEY_get_base_id(pkey)`.

`EVP_PKEY_set1_engine()` is typically used by an `ENGINE` returning an HSM key as part of its routine to load a private key.

RETURN VALUES

`EVP_PKEY_set1_RSA()`, `EVP_PKEY_set1_DSA()`, `EVP_PKEY_set1_DH()` and `EVP_PKEY_set1_EC_KEY()` return 1 for success or 0 for failure.

`EVP_PKEY_get1_RSA()`, `EVP_PKEY_get1_DSA()`, `EVP_PKEY_get1_DH()` and `EVP_PKEY_get1_EC_KEY()` return the referenced key or NULL if an error

occurred.

EVP_PKEY_assign_RSA(), EVP_PKEY_assign_DSA(), EVP_PKEY_assign_DH(),
EVP_PKEY_assign_EC_KEY(), EVP_PKEY_assign_POLY1305() and
EVP_PKEY_assign_SIPHASH() return 1 for success and 0 for failure.

EVP_PKEY_get_base_id(), EVP_PKEY_get_id() and EVP_PKEY_type() return a
key type or NID_undef (equivalently EVP_PKEY_NONE) on error.

EVP_PKEY_set1_engine() returns 1 for success and 0 for failure.

SEE ALSO

EVP_PKEY_new(3), SM2(7)

HISTORY

The EVP_PKEY_id() and EVP_PKEY_base_id() functions were renamed to
include "get" in their names in OpenSSL 3.0, respectively. The old
names are kept as non-deprecated alias macros.

EVP_PKEY_set1_RSA, EVP_PKEY_set1_DSA, EVP_PKEY_set1_DH,
EVP_PKEY_set1_EC_KEY, EVP_PKEY_get1_RSA, EVP_PKEY_get1_DSA,
EVP_PKEY_get1_DH, EVP_PKEY_get1_EC_KEY, EVP_PKEY_get0_RSA,
EVP_PKEY_get0_DSA, EVP_PKEY_get0_DH, EVP_PKEY_get0_EC_KEY,
EVP_PKEY_assign_RSA, EVP_PKEY_assign_DSA, EVP_PKEY_assign_DH,
EVP_PKEY_assign_EC_KEY, EVP_PKEY_assign_POLY1305,
EVP_PKEY_assign_SIPHASH, EVP_PKEY_get0_hmac, EVP_PKEY_get0_poly1305,
EVP_PKEY_get0_siphhash, EVP_PKEY_set1_engine and EVP_PKEY_get0_engine
were deprecated in OpenSSL 3.0.

The return value from EVP_PKEY_get0_RSA, EVP_PKEY_get0_DSA,
EVP_PKEY_get0_DH, EVP_PKEY_get0_EC_KEY were made const in OpenSSL 3.0.

The function EVP_PKEY_set_alias_type() was previously documented on
this page. It was removed in OpenSSL 3.0.

COPYRIGHT

Copyright 2002-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use
this file except in compliance with the License. You can obtain a copy
in the file LICENSE in the source distribution or at

<<https://www.openssl.org/source/license.html>>.